



**F - 1425**

# Asphalt Release

**SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947**



## ***ASPHALT RELEASE AGENT***

An economical, highly concentrated, water reducible release agent for both low oil and high oil asphalt products. Simply adjust water dilution for desired results. Biodegradable and may be legally sewered. Does not compromise asphalts sticking to road surface. Contains no silicone or petroleum solvents.

Rev. 03-15-04

Toll Free: 800-238-5150  
Local: 901-363-4340  
Fax: 901-375-3600

**Delta Foremost Chemical Corp.**  
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:  
[www.deltaforemost.com](http://www.deltaforemost.com)



# TECHNICAL DATA

## FOREMOST F-1425 ASPHALT RELEASE

Rev. 8-16-18

**DESCRIPTION:** A clear amber viscous saponified oil designed for release of conventional and modified asphalt from truck beds, rakes and shovels and other asphalt handling equipment.

**APPLICATION:** Recommended for use with both conventional and polymer modified asphalt in construction of roads, highways, and driveways. Assures virtually 100% discharge of asphalt from beds of trucks when used according to directions.

**DIRECTIONS:** Dilute Foremost F-1425 10:1 to 20:1 with water for use with unmodified asphalt. For polymer modified asphalt, dilution rates of 5:1 to 10:1 are recommended.

**PRECAUTIONS:** KEEP OUT OF REACH OF CHILDREN. Combustible, keep container closed. Contains isopropyl alcohol. Keep away from heat, sparks, and flame. Use with adequate ventilation. Do not take internally. May cause eye irritation. Avoid contact with eyes. Wash thoroughly after handling.

**FIRST AID:** In case of contact with eyes, immediately flush eyes with plenty of water. Get medical attention if burning persists.

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.

### FACTS

1. Water Soluble
2. Water Dilutable
3. Low Foaming

### BENEFITS

1. Non Emulsion Separation
2. Maximum economy to user, Easy clean-up of forms and molds
3. Uniform coverage of forms