



SAFETY DATA SHEET

Revision Date 6-October-2014

Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name F-2137-ES Sure Step Brown

UN/ID No UN1866
Product Code F-2137-ES

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Paint

Details of the Supplier of the Safety Data Sheet

Supplier Address

Delta Foremost Chemical Corporation
3915 Air Park St.
Memphis, Tennessee 38118

Emergency Telephone Number

Company Phone Number (901) 363-4340
Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Flammable liquids	Category 2

Signal Word

DANGER

Hazard Statements

Causes skin irritation
Causes serious eye irritation
Highly flammable liquid and vapor



Appearance Brown liquid

Physical State Liquid

Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
If skin irritation persists: Get medical advice/attention
In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects
Toxic to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Xylene	1330-20-7	Proprietary

Product contains a proprietary mixture of ingredients.

4. FIRST AID MEASURES**First Aid Measures**

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.
Inhalation	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison center if individual's condition declines or if symptoms persist.
Ingestion	Do NOT induce vomiting. Immediate medical attention is required.

Most Important Symptoms and Effects, both Acute and Delayed

Symptoms	Nausea, dizziness, irritation to skin and/or mucous membranes.
-----------------	----------------------------------------------------------------

Indication of any Immediate Medical Attention and Special Treatment Needed**Note to Physicians**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Foam, carbon dioxide, dry chemical extinguisher, or water spray.

Unsuitable Extinguishing Media Water jet.**Specific Hazards Arising from the Chemical**

Flammable/combustible material. May be ignited by heat, sparks or flames. Vapors may travel to source of ignition and flash back. Container may explode in heat or fire.

Hazardous Combustion Products Carbon monoxide.**Sensitivity to Static Discharge** Flammable mixtures of this product are readily ignited even by static discharge.**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Water may be used to cool closed containers to prevent pressure buildups and possible ignition or explosion when exposed to extreme heat. Use air-supplied equipment for enclosed areas.

6. ACCIDENTAL RELEASE MEASURES**Personal Precautions, Protective Equipment and Emergency Procedures****Personal Precautions**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). In case of a spill, clear the affected area and protect people. Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

Methods and Material for Containment and Cleaning Up**Methods for Containment**

For small spills, absorb on polypads or other suitable non-reactive absorbent materials. For large spills, dike far ahead of spill for later disposal. Absorb with materials such as: non-combustible material, cat litter / sand.

Methods for Cleaning Up

Use clean non-sparking tools to collect absorbed material. Sweep up absorbed material and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE**Precautions for Safe Handling****Advice on Safe Handling**

Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Ensure containers are properly labeled. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Wash face, hands, and any exposed skin thoroughly after handling. When using do not eat, drink or smoke. Keep containers closed when not in use. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharges. Ground all equipment to prevent buildup of static charge.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Materials Strong oxidizers such as permanganate.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-

Appropriate Engineering Controls

Engineering Controls Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection Splash goggles or safety glasses.

Skin and Body Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory Protection Solvent type mask.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on Basic Physical and Chemical Properties**

Physical State	Liquid	Odor	Solvent
Appearance	Brown liquid	Odor Threshold	Not determined
Color	Brown		

Property	Values	Remarks • Method
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	142.77 °C / 289 °F	
Flash Point	27.22 °C / 81 °F	Tag Closed Cup
Evaporation Rate	11.5	(butyl acetate = 1)
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	7.0%	
Lower Flammability Limit	1.0%	
Vapor Pressure	7 (mm Hg)	
Vapor Density	3.7	(Air=1)
Specific Gravity	1.255	(1=Water)
Water Solubility	Insoluble in water	
Solubility in Other Solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	

Dynamic Viscosity	Not determined
Explosive Properties	Not determined
Oxidizing Properties	Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep away from oxidizers, heat and open flame.

Incompatible Materials

Strong oxidizers such as permanganate.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation.
Inhalation	Over-exposure to vapors could result in upper respiratory tract irritation.
Ingestion	Ingestion may cause irritation to mucous membranes.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 47635 mg/L (Rat) 4 h

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7		Group 3		

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

Numerical Measures of Toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic organisms. Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Xylene 1330-20-7		13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 0.0084 mg/L 24 h	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50

Persistence and Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Chemical Name	Partition Coefficient
Xylene 1330-20-7	2.77 - 3.15

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		Included in waste stream: F039		U239

Chemical Name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1866
 Proper Shipping Name Resin Solution
 Hazard Class 3
 Packing Group II
 Reportable Quantity (RQ) 1000lbs for Xylene

IATA

UN/ID No UN1866
 Proper Shipping Name Resin Solution
 Hazard Class 3
 Packing Group II

IMDG

UN/ID No UN1866
 Proper Shipping Name Resin Solution
 Hazard Class 3
 Packing Group II

15. REGULATORY INFORMATION

International Inventories

Not Determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Fire hazard	Yes

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	Proprietary	1.0

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7 (Proprietary)	100 lb			X

US State Regulations**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	X	X	X

Regulatory Symbol(s)**16. OTHER INFORMATION**

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	2	3	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	2	3	0	Not determined

Revision Date	6-October-2014
Revision Note	New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet