

# **SAFETY DATA SHEET**

Revision Date 6-October-2014

Version 1

# 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier** 

Product Name F-2290-ES Anti-Slip (OCC Tan)

UN/ID No UN1866 Product Code F-2290-ES

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Paint

**Details of the Supplier of the Safety Data Sheet** 

**Supplier Address** 

Delta Foremost Chemical Corporation

3915 Air Park St.

Memphis, Tennessee 38118

**Emergency Telephone Number** 

Company Phone Number (901) 363-4340

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

# 2. HAZARDS IDENTIFICATION

## **Classification**

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Flammable liquids	Category 2

# Signal Word DANGER

# **Hazard Statements**

Causes skin irritation
Causes serious eye irritation
Highly flammable liquid and vapor



Appearance Tan liquid Physical State Liquid Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof equipment

Use only non-sparking tools

Take precautionary measures against static discharge

#### **Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

If skin irritation persists: Get medical advice/attention

In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store in a well-ventilated place.

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Other Hazards**

Toxic to aquatic life with long lasting effects

Toxic to aquatic life

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Xylene	1330-20-7	Proprietary

Product contains a proprietary mixture of ingredients.

# 4. FIRST AID MEASURES

# **First Aid Measures**

**General Advice** Provide this SDS to medical personnel for treatment.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If

eye irritation persists: Get medical advice/attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If irritation persists, seek

medical attention.

Inhalation Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison

center if individual's condition declines or if symptoms persist.

**Ingestion** Do NOT induce vomiting. Immediate medical attention is required.

### Most Important Symptoms and Effects, both Acute and Delayed

**Symptoms** Nausea, dizziness, irritation to skin and/or mucous membranes.

#### Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Foam, carbon dioxide, dry chemical extinguisher, or water spray.

Unsuitable Extinguishing Media Water jet.

### **Specific Hazards Arising from the Chemical**

Flammable/combustible material. May be ignited by heat, sparks or flames. Vapors may travel to source of ignition and flash back. Container may explode in heat or fire.

Hazardous Combustion Products Carbon monoxide.

**Sensitivity to Static Discharge** Flammable mixtures of this product are readily ignited even by static discharge.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Water may be used to cool closed containers to prevent pressure buildups and possible ignition or explosion when exposed to extreme heat. Use air-supplied equipment for enclosed areas.

### 6. ACCIDENTAL RELEASE MEASURES

# Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). In

case of a spill, clear the affected area and protect people. Wear protective clothing as

described in Section 8 of this safety data sheet.

**Environmental Precautions** Prevent entry into waterways, sewers, basements or confined areas.

# Methods and Material for Containment and Cleaning Up

**Methods for Containment** For small spills, absorb on polypads or other suitable non-reactive absorbent materials. For

large spills, dike far ahead of spill for later disposal. Absorb with materials such as: non-

combustible material, cat litter / sand.

Methods for Cleaning Up

Use clean non-sparking tools to collect absorbed material. Sweep up absorbed material

and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste

disposal, see section 13 of the SDS.

# 7. HANDLING AND STORAGE

#### **Precautions for Safe Handling**

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Ensure containers are properly labeled. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Wash face, hands, and any exposed skin thoroughly after handling. When using do not eat, drink or smoke. Keep containers closed when not in use. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharges. Ground all equipment to prevent buildup of static charge.

### Conditions for Safe Storage, Including any Incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible Materials** Strong oxidizers such as permanganate.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene	STEL: 150 ppm	TWA: 100 ppm	•
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m <sup>3</sup>	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m <sup>3</sup>	

#### **Appropriate Engineering Controls**

**Engineering Controls**Ventilation must be adequate to maintain the ambient workplace atmosphere below the

exposure limit(s) outlined in the SDS.

## Individual Protection Measures, such as Personal Protective Equipment

**Eye/Face Protection** Splash goggles or safety glasses.

**Skin and Body Protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

**Respiratory Protection** Solvent type mask.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on Basic Physical and Chemical Properties

Physical State Liquid

AppearanceTan liquidOdorSolventColorTanOdor ThresholdNot determined

Property Values Remarks • Method

pH Not determined
Melting Point/Freezing Point Not determined

Boiling Point/Boiling Range 142.77 °C / 289 °F Flash Point 27.22 °C / 81 °F

Flash Point 27.22 °C / 81 °F Tag Closed Cup Evaporation Rate 11.5 (butyl acetate = 1)

Flammability (Solid, Gas)

Not determined

Upper Flammability Limits7.0%Lower Flammability Limit1.0%Vapor Pressure7 (mm Hg)Vapor Density3.7

 Vapor Density
 3.7
 (Air=1)

 Specific Gravity
 1.255
 (1=Water)

 Water Solvbiller
 Insolvble in water

Water Solubility
Solubility in Other Solvents
Partition Coefficient
Autoignition Temperature
Decomposition Temperature
Kinematic Viscosity
Insoluble in water
Not determined
Not determined
Not determined
Not determined

Dynamic Viscosity

Explosive Properties

Oxidizing Properties

Not determined

Not determined

# 10. STABILITY AND REACTIVITY

# Reactivity

Not reactive under normal conditions.

#### **Chemical Stability**

Stable under recommended storage conditions.

### **Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization** Hazardous polymerization does not occur.

#### **Conditions to Avoid**

Keep away from oxidizers, heat and open flame.

#### **Incompatible Materials**

Strong oxidizers such as permanganate.

### **Hazardous Decomposition Products**

None known based on information supplied.

# 11. TOXICOLOGICAL INFORMATION

#### Information on Likely Routes of Exposure

**Product Information** 

**Eye Contact** Causes serious eye irritation.

**Skin Contact** Causes skin irritation.

**Inhalation** Over-exposure to vapors could result in upper respiratory tract irritation.

**Ingestion** Ingestion may cause irritation to mucous membranes.

## **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg ( Rabbit )	= 5000 ppm (Rat)4 h = 47635 mg/L (Rat)4 h

# Information on Physical, Chemical and Toxicological Effects

**Symptoms** Please see section 4 of this SDS for symptoms.

# Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene		Group 3		
1330-20-7				

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

# **Numerical Measures of Toxicity**

Not determined

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

Toxic to aquatic organisms. Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Xylene		13.4: 96 h Pimephales	EC50 = 0.0084 mg/L 24 h	3.82: 48 h water flea mg/L
1330-20-7		promelas mg/L LC50 flow-		EC50 0.6: 48 h Gammarus
		through 2.661 - 4.093: 96 h		lacustris mg/L LC50
		Oncorhynchus mykiss mg/L		
		LC50 static 13.5 - 17.3: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 13.1 - 16.5: 96 h		
		Lepomis macrochirus mg/L		
		LC50 flow-through 19: 96 h		
		Lepomis macrochirus mg/L		
		LC50 7.711 - 9.591: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static 23.53 - 29.97: 96		
		h Pimephales promelas mg/L		
		LC50 static 780: 96 h		
		Cyprinus carpio mg/L LC50		
		semi-static 780: 96 h		
		Cyprinus carpio mg/L LC50		
		30.26 - 40.75: 96 h Poecilia		
		reticulata mg/L LC50 static		

# Persistence and Degradability

Not determined

# **Bioaccumulation**

Not determined

# **Mobility**

Chemical Name	Partition Coefficient
Xylene	2.77 - 3.15
1330-20-7	

# **Other Adverse Effects**

Not determined

# 13. DISPOSAL CONSIDERATIONS

# **Waste Treatment Methods**

**Disposal of Wastes**Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene		Included in waste stream:		U239
1330-20-7		F039		

Chemical Name	California Hazardous Waste Status
Xylene	Toxic
1330-20-7	Ignitable

# 14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

**DOT** 

UN/ID No UN1866
Proper Shipping Name Resin Solution

Hazard Class 3
Packing Group II

Reportable Quantity (RQ) 1000lbs for Xylene

**IATA** 

UN/ID No UN1866
Proper Shipping Name Resin Solution

Hazard Class 3
Packing Group II

**IMDG** 

UN/ID No UN1866
Proper Shipping Name Resin Solution

Hazard Class 3
Packing Group ||

# 15. REGULATORY INFORMATION

### **International Inventories**

Not Determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

## **US Federal Regulations**

## **CERCLA**

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb		RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ

## SARA 311/312 Hazard Categories

Acute health hazard Yes Fire hazard Yes

# **SARA 313**

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	Proprietary	1.0

# **CWA (Clean Water Act**

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene	100 lb			X
1330-20-7 ( Proprietary )				

### **US State Regulations**

### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylene	X	X	X
1330-20-7			

# Regulatory Symbol(s)

16. OTHER INFORMATION					
<u>NFPA</u>	Health Hazards	Flammability	Instability ∩	Special Hazards Not determined	
<u>HMIS</u>	Health Hazards 2	Flammability 3	<b>Physical Hazards</b> 0	Personal Protection Not determined	

**Revision Date** 6-October-2014 **Revision Note** New format

#### <u>Disclaimer</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

\_\_\_\_\_\_