

SAFETY DATA SHEET

Revision Date 16-Nov-2016

Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier Product Name

F-2437-ES Sure Step – Sunbelt Green

UN/ID No Product Code

UN1866 F-2437-ES

 Recommended Use of the Chemical and Restrictions on Use

 Recommended Use
 Paint

Details of the Supplier of the Safety Data Sheet Supplier Address Delta Foremost Chemical Corporation 3915 Air Park St. Memphis, Tennessee 38118

Emergency Telephone Number Company Phone Number Emergency Telephone

(901) 363-4340 INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Flammable liquids	Category 2

Signal Word DANGER

Hazard Statements

Causes skin irritation Causes serious eye irritation Highly flammable liquid and vapor



Appearance Bright green liquid

Physical State Liquid

Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof equipment Use only non-sparking tools Take precautionary measures against static discharge

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation persists: Get medical advice/attention. In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects Toxic to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Xylene	1330-20-7	Proprietary

Product contains a proprietary mixture of ingredients.

4. FIRST AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.
Inhalation	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison center if individual's condition declines or if symptoms persist.
Ingestion	Do NOT induce vomiting. Immediate medical attention is required.
Most Important Symptoms and Effe	ects, both Acute and Delayed
Symptoms	Nausea, dizziness, irritation to skin and/or mucous membranes.
Indication of any Immediate Medica	I Attention and Special Treatment Needed
Note to Dissistence	— • • • • •

Note to Physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam, carbon dioxide, dry chemical extinguisher, or water spray.

Unsuitable Extinguishing Media Water jet.

Specific Hazards Arising from the Chemical

Flammable/combustible material. May be ignited by heat, sparks or flames. Vapors may travel to source of ignition and flash back. Container may explode in heat or fire.

Hazardous Combustion Products Carbon monoxide.

Sensitivity to Static Discharge Flammable mixtures of this product are readily ignited even by static discharge.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Water may be used to cool closed containers to prevent pressure buildups and possible ignition or explosion when exposed to extreme heat. Use air-supplied equipment for enclosed areas.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). In case of a spill, clear the affected area and protect people. Wear protective clothing as described in Section 8 of this safety data sheet.
Environmental Precautions	Prevent entry into waterways, sewers, basements or confined areas.
Methods and Material for Containm	ent and Cleaning Up
Methods for Containment	For small spills, absorb on polypads or other suitable non-reactive absorbent materials. For large spills, dike far ahead of spill for later disposal. Absorb with materials such as: non-combustible material, cat litter / sand.
Methods for Cleaning Up	Use clean non-sparking tools to collect absorbed material. Sweep up absorbed material and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Ensure containers are properly labeled. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Wash face, hands, and any exposed skin thoroughly after handling. When using do not eat, drink or smoke. Keep containers closed when not in use. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharges. Ground all equipment to prevent buildup of static charge.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place.
Incompatible Materials	Strong oxidizers such as permanganate.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm	-
		(vacated) STEL: 655 mg/m ³	

Appropriate Engineering Controls

Engineering Controls	Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS.
Individual Protection Measures,	such as Personal Protective Equipment
Eye/Face Protection	Splash goggles or safety glasses.
Skin and Body Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Respiratory Protection	Solvent type mask.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Appearance Color	Liquid Bright green liquid Bright green	Odor Odor Threshold	Solvent Not determined
<u>Property</u> pH Melting Point/Freezing Point Boiling Point/Boiling Range	<u>Values</u> Not determined Not determined 142.77 °C / 289 °F	<u>Remarks • Method</u>	
Flash Point Evaporation Rate Flammability (Solid, Gas) Upper Flammability Limits Lower Flammability Limit	27.22 °C / 81 °F 11.5 Not determined 7.0% 1.0%	Tag Closed Cup (butyl acetate = 1)	
Vapor Pressure Vapor Density Specific Gravity	7 (mm Hg) 3.7 1.319	(Air=1) (1=Water)	
Water Solubility Solubility in Other Solvents Partition Coefficient Autoignition Temperature Decomposition Temperature	Insoluble in water Not determined Not determined Not determined Not determined		
Kinematic Viscosity Dynamic Viscosity Explosive Properties Oxidizing Properties	Not determined Not determined Not determined Not determined		

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Keep away from oxidizers, heat and open flame.

Incompatible Materials

Strong oxidizers such as permanganate.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information	
Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation.
Inhalation	Over-exposure to vapors could result in upper respiratory tract irritation.
Ingestion	Ingestion may cause irritation to mucous membranes.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene	= 4,300 mg/kg (Rat)	> 1,700 mg/kg (Rabbit)	= 5,000 ppm (Rat) 4 h
1330-20-7			= 47,635 mg/L (Rat)4 h

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Card	cinoger	hicity
Cart	inogei	licity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene		Group 3		
1330-20-7				

IARC (International Agency for Research on Cancer) Group 3 IARC components are "not classifiable as human carcinogens"

Numerical Measures of Toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic organisms. Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Xylene		13.4: 96 h Pimephales	EC50 = 0.0084 mg/L 24 h	3.82: 48 h water flea mg/L
1330-20-7		promelas mg/L LC50 flow-		EC50 0.6: 48 h Gammarus
		through 2.661 - 4.093: 96 h		lacustris mg/L LC50
		Oncorhynchus mykiss mg/L		
		LC50 static 13.5 - 17.3: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 13.1 - 16.5: 96 h		
		Lepomis macrochirus mg/L		
		LC50 flow-through 19: 96 h		
		Lepomis macrochirus mg/L		
		LC50 7.711 - 9.591: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static 23.53 - 29.97: 96		
		h Pimephales promelas mg/L		
		LC50 static 780: 96 h		
		Cyprinus carpio mg/L LC50		
		semi-static 780: 96 h		
		Cyprinus carpio mg/L LC50		
		30.26 - 40.75: 96 h Poecilia		
		reticulata mg/L LC50 static		

Persistence and Degradability

Not determined

Bioaccumulation

Not determined

<u>Mobility</u>

Chemical Name	Partition Coefficient
Xylene	2.77 - 3.15
1330-20-7	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene		Included in waste stream:		U239
1330-20-7		F039		

Chemical Name	California Hazardous Waste Status
Xylene	Toxic
1330-20-7	Ignitable

14. TRANSPORT INFORMATION

<u>Note</u>

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT	
UN/ID No	UN1866
Proper Shipping Name	Resin Solution
Hazard Class	3
Packing Group	II
Reportable Quantity (RQ)	1000lbs for Xylene
ΙΑΤΑ	
UN/ID No	UN1866
Proper Shipping Name	Resin Solution
Hazard Class	3
Packing Group	11
IMDG	
UN/ID No	UN1866
Proper Shipping Name	Resin Solution

15. REGULATORY INFORMATION

International Inventories

Hazard Class

Packing Group

Not Determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

3

Ш

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb		RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Fire hazard	Yes

<u>SARA 313</u>

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene	1330-20-7	Proprietary	1.0

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb			Х

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylene	Х	Х	Х
1330-20-7			

16. OTHER INFORMATION				
<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	2	3	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	2	3	0	Not determined

Revision Date	16-Nov-2016
Revision Note	New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet