



FM 1010B-ES OVERSPRAY AWAY

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

OVERSPRAY REMOVER FOR INDUSTRIAL EQUIPMENT



Apply to Surface



Pressure Wash After
Adequate Exposure



Ready to Rent

ENVIRONMENTALLY SAFE—No methylene chloride, no chlorinated solvents, no HAPS, biodegradable.

EASY APPLICATION—Ready to use solution easily applied through FM 8359 All Purpose Sprayer or typical garden-type sprayer.

FAST— Starts to dissolve overspray after 5 to 20 minutes exposure.

RECOMMENDED—for removal of paint overspray and dryfall from lift equipment surfaces and decals. Removes residual adhesive from old decals.

DECREASE TURN AROUND TIME—Allows equipment to get back in the field quicker with less shop time. Keeps your investment producing.

SAFE FOR PERSONNEL—Nonflammable, no objectionable odor or fumes, noncaustic, nonacidic.

Note: Recommended only for original factory finishes on industrial equipment. Not intended for use on automotive finishes. Some factory finishes are less durable and may be subject to attack. Always test first in an inconspicuous area on plastic and painted surfaces. Manufacturer not liable for misuse or failure of user to thoroughly test.

Packed in 55 Gallon Drums and Cases of 48 Quarts.

Rev. 8-28-14

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com





TECHNICAL DATA

FOREMOST 1010B-ES OVERSPRAY AWAY

Rev. 8-10-16

DESCRIPTION: FM 1010B-ES is a highly efficient liquid product designed for removing overspray of paints, drywall and deposits of glue from most types of surfaces. It is harmless to aluminum and other soft metals and contains no methylene chloride, phenols, chromates or phosphates, which may be objectionable as pollutants.

APPLICATION: For removal of overspray of relatively hard and difficult to remove paints, such as alkyl, acrylic, any latex paint, etc., as well as most glues and inks. Recommended only for use to remove overspray from aerial equipment and other rental equipment with original sound paint. FM 1010B-ES is especially useful for removing polyester gel coats and other polyester films.

DIRECTIONS: FM 1010B-ES is ready to use - do not dilute. Apply through trigger sprayer or pump sprayer to overspray and allow to sit for 10-30 minutes. Pressure rinse - repeat as needed until all overspray is removed. Do not use on equipment that has already been sandblasted and repainted. No neutralizing is required.

Steel parts should be thoroughly rinsed after removing from FM 1010B-ES to prevent rusting. If painting or phosphatizing is to follow, clean with a mild detergent to remove all traces of residue.

Care should be taken when exposing FM 1010B-ES to any plastic surface as damage may result. Be sure to spot-test an area before proceeding.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** Do not take internally. If ingested, get immediate medical attention. Use with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin and eyes. Contact with skin can cause moderate irritation, defatting or dermatitis. Keep container closed when not in use.

FIRST AID: EYES: Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention. **SKIN:** Wash thoroughly with soap or mild detergent and water. **INGESTION:** Get medical attention immediately. **INHALATION:** If affected, move individual to fresh air. If breathing is difficult, administer oxygen.

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.

FACTS

1. Contains no phenols or methylene chloride
2. Strips fast
3. Long-Lasting
4. Safe for all metals
5. Ready to use, easy

BENEFITS

1. Eliminates pollution problems
2. Through-put may be increased
3. Harmless to items being stripped
4. No complicated mixing or set-up procedures
5. No foul odors