



SPECIALTIES FOR MAINTENANCE & SANITATION SINCE 1947

THE DIP

FM 1012

- FAST-PENETRATING
- RAPID BREAKDOWN OF COATINGS
- WORKS QUICKLY ON HEAVY BUILDUP
- REDUCES DWELL TIME
- EXPEDITES UP STRIPPING PROCESS

REMOVAL APPLICATIONS

- MULTIPLE LAYERS OF PAINT
- INDUSTRIAL VARNISHES / FINISHES
- HEAVY GRIME AND BUILDUP
- ASPHALT & TAR-BASED DEPOSITS
- BAKED-ON & STUBBORN COATINGS
- GREAT FOR ALUMINUM, BABBITT, POT METALS, BRASS, COPPER, IRON & STEEL

SIMPLE — The Dip easily strips clean by immersion, followed by a water or petroleum solvent rinse.

FAST — The Dip out-muscles stubborn coatings, saving hours of waiting time with unsurpassed solvent action. Rapid high impact is retained over extended use cycles.

RECOMMENDED FOR — City and Highway Department sign shops, and shops of Aircraft, Railroad, Fleet Maintenance, Shipyard, Farm and Heavy Equipment industries. Anywhere economical removal of difficult applied film and paints (such as epoxy, acrylic, baked enamel, or lacquer) is required.

NOTE — Not recommended for Magnesium Alloys. This product does not contain phenols, phosphates, methylene chloride, or chromates.



PACKAGED IN 55 GAL DRUMS & 5 GAL PAILS

< FM 8369 DIPPING BASKET



Contact Us



t 1.800.238.5150
f 1.901.375.3600



sales@deltaforemost.com
deltaforemost.com



3915 Air Park Street
Memphis, TN 38118



TECHNICAL DATA

FM 1012 THE DIP

Rev. 4-2-26

DESCRIPTION: Delta Foremost's FM 1012 The Dip is a non-methylene chloride, cold tank-type stripper formulated to remove paints, epoxies, urethanes, powder coatings, oil, grease, and other difficult-to-remove coating systems.

APPLICATION: Recommended for use in cold soak vat operations where maximum protection of the underlying substrate is required.

DIRECTIONS: **SOAK TANK:** Use full strength; do not dilute. Submerge parts and allow to soak 15–45 minutes, or until the coating loosens or lifts. The finish should bubble or separate in sheets. Remove loosened paint with a pressure washer, scraper, or stiff brush. Clean any remaining residue with mild soapy water, mineral spirits, or alcohol.

FM 8369 Dipping Baskets available for submerging smaller items into our 5 gallon pail packaging.

PRECAUTIONS: **EXTREMELY FLAMMABLE.** Keep away from heat, sparks, open flames, and hot surfaces. Vapors are heavier than air and may travel along the ground to distant ignition sources, including pilot lights and electric motors, and flash back to the container. Use only in well-ventilated areas or outdoors to prevent hazardous vapor accumulation.

FIRST AID: EYES: Immediately flush with large amounts of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Seek medical attention. **SKIN:** Wash thoroughly with soap or mild detergent and water. If irritation develops or persists, seek medical attention. **INHALATION:** Remove person to fresh air. If breathing is difficult, administer oxygen by qualified personnel. Seek immediate medical attention. Before using this product, read the Safety Data Sheet (SDS) for complete safety information.