



**1039**

## **E-Z STRIP COAT**

**SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947**



Masks booths in minutes—when overspray accumulates, simply score and peel off.

## **CUT OVERHEAD COSTS**

**REMOVE OVERSPRAY  
FROM PAINT BOOTHS  
IN MINUTES**

## **REDUCES FIRE HAZARDS!**

**EASY-TO-PEEL**—Coatings will not age. This high strength plastic film stays flexible and wall-gripping. Actually, Foremost 1039 simplifies and makes booth cleaning so easy and fast you gladly remove overspray often, thereby reducing overall fire danger.

**BETTER LIGHTING**—White background reflects light for greater visibility—better working conditions and painting quality.

**ECONOMICAL**—Approximately 150-200 sq. ft. per gallon coverage. Easy to apply, easy to remove. Use regular spray equipment. Nothing to add. Retains tensile strength. Many so-called peelable coatings, in fact, have to be flaked or scraped off.

**NEW Foremost 1039** removes dried overspray from paint booths in minutes instead of hours. Takes only minutes to re-coat with Foremost 1039. Resume painting within 20 minutes or less.

### **OTHER USES INCLUDE —**

1. Strip coating for furniture manufacturing and metal fabricating industries.
2. Temporary coating to protect tools, machinery, parts, etc.

**NOTE:** Not for use on painted surfaces or wood.

**Packed in 55 Gallon Steel Drums**

Rev. 1-18-19

Toll Free: 800-238-5150  
Local: 901-363-4340  
Fax: 901-375-3600

**Delta Foremost Chemical Corp.**  
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:  
[www.deltaforemost.com](http://www.deltaforemost.com)





# TECHNICAL DATA

## FOREMOST 1039 E-Z STRIP COAT

Rev. 1-18-19

**DESCRIPTION:** A sprayable white liquid which forms a high-strength, peelable plastic film on spray booth walls to allow easy removal of overspray accumulations. This product provides low toxicity, is rapid drying and after the solvent system has evaporated, the remaining plastic coating is non-flammable. Its non-greasy surfaces do not age, stay flexible, reflect light, resist acids, alkalies, fats, alcohols, and gasoline.

**APPLICATION:** In addition to paint spray booth applications, the product may also be used as temporary coating to protect silverware, tools, machine parts or to provide a strip coating for furniture manufacturers. **NOTE:** This is for all unpainted metal and/or smoothly troweled masonry surfaces only.

**DIRECTIONS:** Usual application is by spraying product as furnished through regular pressure pot equipment or cup gun. Brushing is less effective method.

When overspray accumulates, merely score the surface and peel off in large sheets.

**PRESSURE POT APPLICATION:** Depending on temperature and thickness of coating begin with approximately 50 psi and adjust spray pattern to accomplish a uniform, wet application with a minimum of cobwebbing.

**CUP GUN APPLICATION:** DeVilbiss and Binks Equipment.

	<b>DeVilbiss</b>	<b>Binks</b>
Spray Gun	MBC-510, JGA-502	#18, #62
Nozzle Combination	704E, 74E, 765E, 78E	63PB, 66PE, 68PB

**PRECAUTIONS:** **KEEP OUT OF REACH OF CHILDREN.** Contains aromatic petroleum distillate. Extremely flammable liquid and vapor. Do not take internally. **MAY BE HARMFUL OR FATAL IF SWALLOWED.** Vapor is harmful. Keep away from heat and open flame. Use with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin and eyes. If ingested, get immediate medical attention. Keep container closed when not in use. Contact with skin can cause moderate irritation, defatting, dermatitis.

**FIRST AID: EYES:** Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention. **SKIN:** Wash thoroughly with soap or mild detergent and water. **INGESTION:** Get immediate medical attention. **INHALATION:** If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.