

SAFETY DATA SHEET

Revision Date 17-April-2015

Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name Foremost 1040 Booth Coat

UN/ID No UN1866 Product Code 1040

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Cleaning agent.

Details of the Supplier of the Safety Data Sheet

Supplier Address

Delta Foremost Chemical Corporation

3915 Air Park St.

Memphis, Tennessee 38118

Emergency Telephone Number

Company Phone Number (901) 363-4340

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Serious Eye Damage/Eye Irritation	Category 2
Skin Irritation	Category 3
Specific target organ toxicity (single exposure)	Category 3
Aspiration Hazard	Category 2
Flammable liquids	Category 2

Signal Word DANGER

Hazard Statements

Causes serious eye irritation
May cause respiratory irritation. May cause drowsiness or dizziness
Highly flammable liquid and vapor
Causes mild skin irritation
May be harmful if swallowed and enters airways



Appearance White liquid Physical State Liquid Odor Solvent

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Acetone	67-64-1	Proprietary
Toluene	108-88-3	Proprietary

Product contains a proprietary mixture of ingredients.

4. FIRST AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If

eye irritation persists: Get medical advice/attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If irritation persists, seek

medical attention.

Inhalation Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison

center if individual's condition declines or if symptoms persist.

Ingestion Do NOT induce vomiting. Immediate medical attention is required.

Most Important Symptoms and Effects, both Acute and Delayed

Symptoms Nausea, dizziness, irritation to skin and/or mucous membranes.

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Alcohol resistant foam, carbon dioxide, or dry chemical.

Unsuitable Extinguishing Media Water may be ineffective, but can be used to protect firemen and cool containers.

Specific Hazards Arising from the Chemical

Flammable/combustible material. May be ignited by heat, sparks or flames. Vapors may travel to source of ignition and flash back. Container may explode in heat or fire.

Hazardous Combustion Products Carbon monoxide.

Sensitivity to Static Discharge Flammable mixtures of this product are readily ignited even by static discharge.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Water may be used to cool closed containers to prevent pressure buildups and possible ignition or explosion when exposed to extreme heat. Use air-supplied equipment for enclosed areas.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). In

case of a spill, clear the affected area and protect people. Wear protective clothing as

described in Section 8 of this safety data sheet.

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and Material for Containment and Cleaning Up

Methods for Containment For small spills, absorb on polypads or other suitable non-reactive absorbent materials. For

large spills, dike far ahead of spill for later disposal. Absorb with materials such as: non-

combustible material, cat litter / sand.

Methods for Cleaning UpUse clean non-sparking tools to collect absorbed material. Sweep up absorbed material

and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste

disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Ensure containers are properly labeled. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Wash face, hands, and any exposed skin thoroughly after handling. When using do not eat, drink or smoke. Keep containers closed when not in use. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharges. Ground all equipment to prevent buildup of static charge. Avoid breathing vapors or mists.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Materials Oxidizing materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	_
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not apply	
		to the cellulose acetate fiber	
		industry. It is in effect for all other	
		sectors	
		(vacated) STEL: 1000 ppm	
Toluene	TWA: 20 ppm	TWA: 200 ppm	TWA: 100 ppm
108-88-3		TWA: 375 mg/m ³	TWA: 375 mg/m ³
		STEL: 150 ppm	STEL: 150 ppm
		STEL: 560 mg/m ³	STEL: 560 mg/m ³

Appropriate Engineering Controls

Engineering Controls Ventilation must be adequate to maintain the ambient workplace atmosphere below the

exposure limit(s) outlined in the SDS.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection Splash goggles or safety glasses.

Skin and Body Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Respiratory Protection Solvent type mask.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Liquid

AppearanceWhite liquidOdorSolvent

ColorWhiteOdor ThresholdNot determined

Property Values Remarks • Method

pH Not determined
Melting Point/Freezing Point Not applicable
Boiling Point/Boiling Range 56.0 °C / 132.8 °F
Flash Point -17.22 °C / 1.0 °F

Evaporation Rate 4.6

Flammability (Solid, Gas) Not determined

Upper Flammability Limits 12.8% Lower Flammability Limit 2.6%

Vapor Pressure 400 (mm Hg) @ 39.5°C, 104°F

(butyl acetate = 1)

 Vapor Density
 36.7
 (Air=1)

 Specific Gravity
 0.899
 (1=Water)

Water Solubility Insoluble in water Solubility in Other Solvents Not determined Not determined **Partition Coefficient Autoignition Temperature** Not determined **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep away from oxidizers, heat and open flame.

Incompatible Materials

Oxidizing materials.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact Causes mild skin irritation.

Inhalation Over-exposure to vapors could result in upper respiratory tract irritation.

Ingestion May be harmful if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	-
Toluene 108-88-3	= 5580 mg/kg (Rat)	= 12196 mg/kg (Rabbit)	= 12500-28800 mg/m³ (Rat) 4h

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA,

IARC or NTP.

STOT - Single Exposure May cause respiratory irritation. May cause drowsiness or dizziness.

Numerical Measures of Toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

There is no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Acetone 67-64-1		4.74 - 6.33: 96 h Oncorhynchus mykiss mg/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	G	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Toluene 108-88-3	245.0: 24 h Chlorella vulgaris mg/L EC50 10.0: 24 h Pseudokirchnieriella subcapitata mg/L EC50	7.63: 96 h Oncorhynchus mykiss mg/L LC50 5.44: 7 d Pimephales promelas mg/L NOEC		8.0: 24 h Daphnia magna mg/L EC50

Persistence and Degradability

Readily biodegradable.

Bioaccumulation

Not determined

Mobility

Chemical Name	Partition Coefficient
Acetone	-0.24
67-64-1	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Acetone	Ignitable
67-64-1	

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT

UN/ID No UN1866
Proper Shipping Name Resin Solution

Hazard Class 3
Packing Group ||

Reportable Quantity (RQ) 5000lbs for Acetone

IATA

UN/ID No UN1866
Proper Shipping Name Resin Solution

Hazard Class 3
Packing Group II

IMDG

UN/ID No UN1866
Proper Shipping Name Resin Solution

Hazard Class 3
Packing Group II

15. REGULATORY INFORMATION

International Inventories

Not Determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

SARA 311/312 Hazard Categories

Acute health hazard Yes Fire hazard Yes

SARA 313

Toluene, CAS No. 108-88-3

US State Regulations

California Proposition 65

Toluene, CAS No. 108-88-3

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	Х	X	X
Toluene 108-88-3	Х	X	X

16 OTHER INCORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	2	3	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	2	3	0	Not determined

Revision Date 17-April-2015 **Revision Note** New format

<u>Disclaimer</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet