



1191 GLUE REMOVER

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947



- **NON-COMBUSTIBLE**
- **NON-CONDUCTIVE**
- **NON-CORROSIVE**

FAST-ACTING, ECONOMICAL, EASY-TO-USE

EASY REMOVAL of adhesive overspray from metal, Formica®, concrete, wood and other surfaces.

SPECIFICALLY FORMULATED for removal of solvent based and most water based contact cements and other adhesives.

REPLACES 1,1,1-Trichloroethane, MEK and other unsafe substances. Contains no ozone depleting chemicals.

**FAST DRYING
LEAVES NO RESIDUES**

IDEALLY SUITED FOR:

- Cabinet Makers and Woodworking Shops
- Mobile Home Manufacturing
- Corrugated Box Converters
- Custom Coach Builders
- Printing Companies
- Box Plants

PACKAGED IN 55 GALLON DRUMS

Rev. 6-12-14

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com





TECHNICAL DATA

FOREMOST 1191 GLUE REMOVER

Rev. 1-18-19

DESCRIPTION: Foremost 1191 Glue Remover is neutral, non-corrosive and non-conductive. Contains no 1,1,1-Trichloroethane, CFC's or other ozone depleting chemicals.

This is a balanced blend of solvents in a ready-to-use form that penetrates and dissolves a broad spectrum of solvent based and most water based glues. It is easy to use and is safe on all metals, wood surfaces, glass, sound paint and insulating varnish. Foremost 1191 Glue Remover is designed to give high performance cleaning, and will evaporate leaving no oily film or residue.

APPLICATION: Recommended for relatively hard and difficult to remove glue from metal, glass or wood surfaces. It is used by industrial, automotive, electrical maintenance shops, food processors and institutions. It is also designed to give high performance cleaning of grease, wax, oils and other foreign matter.

DIRECTIONS:

1. Spray or pour Foremost 1191 Glue Remover on surfaces using a heavy wet pattern. A second application may be necessary for more stubborn soils.
2. Flush rinse with a second application.
3. Dry off by air blast, wiping or allow to dry.

VAT CLEANING:

1. Fill the vat with Foremost 1191 Glue Remover.
2. Immerse articles to be cleaned in the cleaner.
3. Let soak for a few minutes.
4. Remove the articles from the vat and dry by means of an air blast or allow to air dry.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** Contains chlorinated and aliphatic solvents. Do not take internally. **MAY BE HARMFUL OR FATAL IF SWALLOWED.** Vapor is harmful. Keep away from heat and open flame. Use with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin and eyes. If ingested, get immediate medical attention. Keep container closed when not in use. Contact with skin can cause moderate irritation, defatting and dermatitis of skin.

FIRST AID: EYES: Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention. **SKIN:** Wash thoroughly with soap or mild detergent and water. **INGESTION:** Get immediate medical attention. **INHALATION:** If affected. Remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Get medical attention.

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.