



1201-ES CUTTING OIL (Aerosol)

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

HIGH PERFORMANCE • SYNTHETIC BLEND



USE WHEN:

- SAWING
- CUTTING
- BORING
- GRINDING
- TAPPING
- MACHINING
- DRILLING
- PUNCHING

THICKENED FORMULA— Clings to tools and surfaces.

COOLS AND LUBRICATES — Cooler tools last longer and distort less. Lubricated work cuts cleaner - Floats away burrs and chips.

PROTECTS— Protects from rust & corrosion.

NO GUMMY RESIDUES — Cleans up with water or oil-based cleaners.

RECOMMENDED FOR:

- Machine Shops
- Maintenance Shops
- Repair Shops
- Tool and Die Makers
- Anywhere Tools Meet Metal

16 Doz. or
4/48 cases

8 Doz. or
2/48 cases

4 Doz. or
1/48 case

(Net Wt. 16 oz.)

Rev. 5-9-14

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com



TECHNICAL DATA

FOREMOST 1201-ES (AEROSOL) CUTTING OIL

Rev. 11-28-17

DESCRIPTION: A heavy duty emulsified oil with maximum cooling ability, excellent lubricity and anti-weld properties. It offers a high degree of emulsion stability and corrosion protection. Its use promotes increased production, longer tool life, and finer surface finishes. The thin film remaining on machine work provides rust protection for a reasonable period of time which frequently eliminates the necessity of further protection during additional manufacturing processes.

APPLICATION: It has a wide range of uses in metal working, cutting and forming operations. It is recommended for use with carbide tipped and high speed machine tools on rough turning, drilling, tapping, reaming, turning, sawing, milling, light and heavy duty grinding and other miscellaneous machinery operations on all types and steel alloys, and other machinable ferrous metals. **NOTE:** Not recommended for use on copper or aluminum.

DIRECTIONS:

1. Shake well before using.
2. Hold nozzle 6 to 8 inches from surface requiring lubrication.
3. Generously spray onto cutting surface or tool.
4. Reapply as necessary to maintain lubrication level.

WARNING: Use only with adequate ventilation. Keep out of reach of children. Avoid excessive inhalation of fumes and repeated or prolonged contact with skin. Contents under pressure. Do not expose to heat or store at temperatures exceeding 120°F. Do not puncture or incinerate container. Wrap empty container and put in trash collection. **FIRST AID: If swallowed:** Do not induce vomiting. Get medical attention immediately. **If inhaled:** Move to fresh air. If breathing has stopped, administer artificial respiration. Get medical attention. **If on skin:** Thoroughly wash with soap and water. Get medical attention if irritation persists. **If in eyes:** Flush with liberal amounts of water, lifting eyelids occasionally. Consult physician. **KEEP OUT OF REACH OF CHILDREN.**

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.