



SPECIALTIES FOR MAINTENANCE
& SANITATION SINCE 1947

FOOD GRADE GREASE PLUS

FM 1205-ES

- MULTI-PURPOSE
- HIGH PURITY
- FOOD GRADE LUBRICANT
- NSF RATING H-1



SPECIFICATIONS

- NLGI GRADE: 2
- TEMP RANGE: - 40° F - 500° F
- PENETRATION: 265-295
- DROPPING POINT: 550°
- TIMKEN OK LOAD: 60 lbs
- FOUR BALL WELD LOAD: 620 kg

1205-ES



CALCIUM SULFONATE — Engineered for extreme pressure properties and high salt and steam resistance.

PROTECTS MACHINERY — With inherent anti-wear and rust/corrosion inhibiting properties. Specialty additives prevent oxidation and provide water resistance.

FOOD GRADE GREASE PLUS — Environmentally friendly and among the most technologically advanced on the market.

AVOID COSTLY SHUTDOWNS — Eliminates the friction that causes premature wear and mechanical breakdown.

RECOMMENDED FOR — Food Processors, Pharmaceutical Companies, Packaging Producers for the food industry and anywhere a high quality food grade grease is required.

PACKAGED 40/14.5OZ TUBES PER CASE



Contact Us



t 1.800.238.5150
f 1.901.375.3600



sales@deltaforemost.com
deltaforemost.com



3915 Air Park Street
Memphis, TN 38118



TECHNICAL DATA

FOREMOST 1205-ES FOOD GRADE GREASE PLUS

Rev. 11-1-16

DESCRIPTION: A multi-purpose, high purity food grade lubricant that provides long lasting grease protection. Withstands heat to 500F. Temperatures above 400F may require periodic reapplication.

APPLICATION: For use by bakeries, bottlers, breweries, canneries, dairies, egg processors, meat and poultry processors, pharmaceutical manufacturers, and food processing and packaging plants.

DIRECTIONS: Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** . Do not take internally. May cause eye irritation. Avoid contact with eyes. Wash thoroughly after handling. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea.

FIRST AID: In case of contact with eyes, immediately flush eyes with plenty of water. Get medical attention if oily film persists. For skin, wash with soap and plenty of water. For ingestion of more than 8 ounces contact physician.

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.

FACTS

1. Lubricates
2. Resists extreme pressure, corrosion and water washout
3. Temperature range of -40F to 500F

BENEFITS

1. Reduces friction and wear
2. Resists throw-off
3. Calcium Sulfonate Based