



1798-ES



SPECIALTIES FOR MAINTENANCE  
& SANITATION SINCE 1947

## ASPHALT REMOVER EZ RINSE

### FM 1798-ES

- QUICKLY PENETRATES ASPHALT BUILD UP
- SAFE FOR PERSONNEL
- MILD ODOR
- WORKS ON TAR, TACK, ASPHALT
- SAFE ON EQUIPMENT

## SPECIFICATIONS

- NON-HAZARDOUS
- NON-TOXIC
- NO PETROLEUM HYDROCARBONS
- BIODEGRADABLE
- ADDITIVES FOR MORE COMPLETE RINSING

**NATURAL** – Plant based formula is safe but effective

**CONVENIENT** – Ready to use formula is easy for personnel to apply

**VERSATILE** – May be used as a cleaner or release agent.

**EMULSIFYING FORMULA** – Mixes with water for more thorough rinsing.

**APPLICATION** – Easily applied through a pump type sprayer. FM 8362 HD Galvanized Steel Sprayer is recommended.

**RECOMMENDED FOR** – Asphalt pavers and plants, roofing companies, asphalt sealing companies, Municipal, County, and State road departments, DOTs, Road building equipment companies and anywhere asphalt and tar build up are a problem.

**PACKAGED IN 55 GALLON DRUMS**



Contact Us



t 1.800.238.5150  
f 1.901.375.3600



sales@deltaforemost.com  
deltaforemost.com



3915 Air Park Street  
Memphis, TN 38118



# TECHNICAL DATA

## FM 1798-ES ASPHALT REMOVER EZ RINSE

Rev. 9-28-17

**DESCRIPTION:** A heavy duty, rinseable, bio-based solvent that meets demanding environmental and performance criteria for the removal of asphalt, road and roofing tar, tack, oils and greases.

**APPLICATION:** This product is recommended for use on paving machines, asphalt oil distributors, tack trucks, shuttle buggies, asphalt milling equipment, portable traffic control devices, barrels and cones. It is also successfully used for removal of roofing tar and asphalt from concrete, stone, brick, tile and other masonry surfaces.

**DIRECTIONS:** For removing asphalt, tack, and tar from surfaces of machinery, industrial equipment, trucks, etc. Apply by spraying or brushing the undiluted concentrate over the surface involved, and pressure rinsing with water. Contact time may be altered to meet specific needs and can usually best be determined by the user. Rinse thoroughly with water until all asphalt residue has been removed. For stubborn deposits, additional applications and/or scraping may be required to assist solvent action.

**PRECAUTIONS:** KEEP OUT OF REACH OF CHILDREN. May cause eye irritation. Avoid contact with eyes. Do not take internally.

**FIRST AID:** In case of contact, immediately flush eyes with large amounts of water until burning ceases. Get medical attention immediately if irritation persists.

Before using this product read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.