

3010 SUPER LUSTRE FINISH

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947



SELF-POLISHING
SCUFF RESISTANT
BEAUTIFUL SHINE

WHAT A DIFFERENCE YOU CAN SEE AFTER USING FOREMOST SUPER LUSTRE FINISH

ONLY FOREMOST SUPER LUSTRE FINISH SHINES LIKE THIS!

GIVES HIGH GLOSS TO FLOORS— WITHOUT BUFFING

FOREMOST SUPER LUSTRE FINISH—imparts new protective beauty to your floors thru new self-polishing, super-gloss qualities.

MANY ENVIABLE FEATURES include: Excellent durability, scuff resistance, anti-slip, water resistance, fast drying and initial high lustre—without buffing or polishing.

EASY-TO-USE—No chore for regular maintenance personnel. Simply apply and let dry to its maximum glossy appearance. Self-leveling, no gap marks or streaks.

ECONOMICAL—The secret to economy is in the "mileage". Occasional spray buffing renews high gloss finish. Lasts longer than low solids content products.

RECOMMENDED FOR —

- Vinyl Tile
- Asphalt Tile
- Rubber Tile
- Linoleum
- Sealed Wood
- Terrazzo
- Sealed Concrete
- Cork Tile

Packed in 55 Gallon Drums

Rev. 3-12-14

Toll Free: 800-238-5150 Local: 901-363-4340 Fax: 901-375-3600

Delta Foremost Chemical Corp.

3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at: www.deltaforemost.com



TECHNICAL DATA

FOREMOST 3010 SUPER LUSTRE FINISH

Rev. 5-26-17

DESCRIPTION:

Foremost 3010 Super Lustre Finish is self-polishing and provides excellent durability, beauty, and protection to floors. It has excellent resistance to scuff marks and dirt in addition to providing slip resistant and water resistant features. Foremost 3010 Super Lustre Finish dries to its maximum glossy appearance without the necessity of buffing.

APPLICATION:

Foremost 3010 Super Lustre Finish is recommended for treating the following types of floors: Linoleum, asphalt tile, rubber tile, vinyl tile, terrazzo, cork tile, concrete, and sealed wood.

Typical Coverage: 350 square feet per gallon depending on method of application.

NOTE: Wood floors should be maintained with Foremost 3010 Super Lustre Finish only when the floor is thoroughly sealed so that the surface is water and alkali proof before application.

DIRECTIONS:

- 1. Strip old wax or finish from floors and clean thoroughly.
- 2. The applicator for applying Foremost 3010 Super Lustre Finish should be lambs wool, cotton, or saran. Use only clean applicators, pails, or pans for application.
- 3. Apply thin, even coat. Avoid puddles. Allow 30 minutes between coats.
- 4. It is not necessary to buff following application. However, after heavy traffic the surface appearance can be improved by buffing.

NOTE: Keep from freezing.

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN. May cause eye and skin irritation. Avoid contact with eyes and prolonged contact with skin. Wash thoroughly after handling. Do not take internally.

FIRST AID: EYES: In case of contact with eyes, flush immediately with plenty of water for at least 15 minutes. **SKIN:** Flush with plenty of water. Get medical attention if irritation persists. Wash contaminated clothing before reuse.

Before using this product read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.

FACTS

- 1. High lustre
- 2. Many Enviable Features
- 3. Easy-To-Use
- 4. Economical

BENEFITS

- Imparts new protective beauty to tile floors through super-gloss qualities.
- Excellent durability, scuff resistant, slip resistant, water resistant, initial high lustre.
- 3. Simply apply and let it dry to its self-polishing maximum gloss appearance.
- 4. The secret is in the "mileage"— 350 sq. ft. coverage per gallon and long life.