



3335 NU-SURFACE

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

ELIMINATES CONCRETE DUST SETTLING ON MACHINES OR MERCHANDISE



PARTIAL COVERAGE



FULL COVERAGE

YEAR 'ROUND PROTECTION FOR ALL CONCRETE FLOORS

Converts Ordinary Factory, Shop Or Warehouse Concrete Into An Attractive Easy To Maintain Floor.

SEALED — Floors are easier to keep clean. Oil, grease and other spillages are not permitted to penetrate and stain and can be wiped or mopped from the sealed non-porous floors easily.

STOPS DETERIORATION — Unsealed floors are perpetually abrading. Proof? Simply sweep a small area - as long as you sweep, you will continue to create cement dust particles indefinitely.

IMPROVED APPEARANCE — Foremost 3335 Nu-Surface dries to a light amber shine. If desired, a higher gloss can be achieved and maintained with a wax or wax-type floor finish.

ECONOMICAL — One coat can provide up to several years protection. It is self-leveling and may be put down with applicator, mop, or squeegee. Heavy traffic walkways can be easily spot-treated, new and old coats blend.

Makes Floors Much Easier To Clean And Maintain

NO-SWEAT FLOOR — Hydrostatic action reduces sweating caused by moisture absorption thru concrete on grade or higher level floor.

SEALS AGAINST PENETRATION OF OIL, SOIL AND MOISTURE

RETARDS SURFACE DETERIORATION

NOTE

Foremost 3335 Nu-Surface protects old floors and the contents of the area. Sealed floors can be swept without the constant dust that sweeping generates on unsealed concrete. Sealing eliminates the damage caused by concrete dust settling on merchandise or machinery.

Recommended for floors more than 6 months old. Smooth floors or chemically hardened floors should be etched for best results.

Packed In 55 Gallon Drums

Rev. 5-26-17

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com





TECHNICAL DATA

FOREMOST 3335 NU-SURFACE

Rev. 5-26-17

DESCRIPTION: A quality product designed for concrete floors in excess of 6 months old. It prevents dusting, staining and deterioration and is fast with excellent moisture and alkali resistance.

APPLICATION: This product is recommended as a sealer for concrete floors. It is a one coat sealer, although multiple coats may be applied for higher gloss. It is especially resistant to alkali and moisture and finds widespread use throughout industry and institutional use. It will prevent dusting and disintegration of the surface due to chemical change within the floor.

Typical Coverage: 250 square feet per gallon depending on method of application.

DIRECTIONS: The following application procedure should be followed for best results:

1. The floor should be thoroughly cleaned to remove all loose dust, soil, wax, grease, oil and other foreign matter. If necessary, a heavy duty concrete cleaner or alkaline solution should be used for this purpose, followed by etching with a dilute solution of acid (1 gallon FM 690 of FM 1090C to 8 gallons water). If this type of cleaning is used, then the floor must be rinsed several times and allowed to dry overnight.
2. A thin, even coat of Foremost 3335 Nu-Surface should be applied at a rate of one gallon per 250 square feet with a lamb's wool applicator or other suitable device.
3. Although the sealer will dry to the touch within 4 hours, traffic should not resume until the following day.
4. When the sealer shows signs of wearing in traffic lanes, around machinery, in doorways, etc., the floor should be thoroughly cleaned and the sealer reapplied in those areas.
5. Allow adequate fresh air to circulate while sealer is drying and avoid extreme high and low temperatures for best results when sealing floors.

NOTE: Smooth floors or chemically hardened floors should be acid etched for best results.

Applicators may be cleaned with Xylol or mineral spirits. Keep container tightly sealed at all times to prevent evaporation and possible thickening.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** Contains petroleum hydrocarbons. Do not take internally. May be harmful or fatal if swallowed. If ingested, get immediate medical attention. Keep away from heat and open flame. Use with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin and eyes. Contact with skin can cause moderate irritation, defatting, or dermatitis. Keep container closed when not in use.

FIRST AID: EYES: Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention. **SKIN:** Wash thoroughly with soap or mild detergent and water. **INGESTION:** Get medical attention immediately. **INHALATION:** If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention.

Before using this product read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.

FACTS

1. Fast drying
2. Easy to apply
3. It's a penetrating sealer
4. Excellent for old floors

BENEFITS

1. Apply at close of day and the next morning full production may resume. Dry to touch within 4 hours. Tack-free in 7 hours.
2. Use conventional lamb's wool applicator, mop or squeegee.
3. It penetrates into the concrete, blocking moisture and preventing dusting. Makes floors easier to keep clean.
4. Its light amber color is especially good for floors that have light and dark spots, giving a more uniform look.