



3375 FLOOR SEAL

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947



Keep that "just waxed" look week after week

**Seals
And
Protects**

COMPOSITION TILE FLOORS

**Extends Life
OF WAXES AND
SYNTHETIC FINISHES**

**Cuts Maintenance
Time And Costs!**

BEAUTY INSURANCE FOR YOUR FLOORS

SEALED — floors are easier to clean and maintain. Dirt and grime are not permitted to penetrate and cause stains. Seals pores and rejuvenates old floors. Keep new floors, NEW.

FOREMOST 3375 — is the perfect foundation or base primer for finish coating of wax or polymers. Helps resist wear and black heel marks. One coat restores color and appearance — dries hard and bright in less than one hour.

EASY — to apply. Just mop on; no lap marks and it's self-leveling. Coverage is 300 to 500 square feet per gallon, depending upon porosity of the floor.

ECONOMICAL — unequalled performance and appearance, combined with high solids content makes Foremost 3375 the best buy. In many cases, this superb floor seal is priced below less desirable products.

Foremost 3375 Floor Seal restores original color and beauty to worn porous tile. Protects new tile.

NOTE

The natural beauty and rich color of worn flooring is brought out by sealing with **Foremost 3375**. Regular waxing with an occasional light buffing or a "gloss-rinse" keeps that new look on your sealed floors. For all types composition flooring — any color, light or dark.

Especially recommended for vinyl, asphalt, linoleum, asphalt-asbestos, vinyl asbestos, rubber, cork and even terrazzo.

Packed In 55 Gallon Drums

Rev. 5-26-17

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com





TECHNICAL DATA

FOREMOST 3375 FLOOR SEAL

Rev. 5-26-17

DESCRIPTION: An emulsion of synthetic resins which contains no wax, varnish, lacquer or materials which could be classified as harmful to composition floors. It is capable of restoring floors to a new appearance, often by a single application, or in extreme cases a second coat will be necessary. It is practically odorless and contains no oils, solvents, or other flammable ingredients. It is ideal for areas requiring a safe non-flammable product.

APPLICATION: Recommended for asphalt, linoleum, and terrazzo type floors (except magnesite), concrete, grease-proof asphalt tile, vinyl and vinyl asbestos floors. It restores new life to faded, dry, and bleached out flooring.

This product also serves as an excellent foundation (primer) for wax, synthetic or polymer finish. In heavy traffic areas, Foremost 3375 Floor Seal, because of its natural toughness and durability will actually increase the performance and extend the life of the wax or synthetic finish. Contains anti-slip agents.

Some brands of vinyl tile may cause this product to remain tacky; apply to only a few tiles and allow to dry. If tacky or not completely hard when dry, do not use on this tile.

Typical Coverage: 350 square feet per gallon depending on method of application.

DIRECTIONS:

1. Remove all old sealers, waxes, polishes, etc.
2. For thorough cleaning, scrubbing with a floor machine, using steel wool or a synthetic scrubbing pad is recommended.
3. Rinse thoroughly to insure the removal of the soap or synthetic cleaners from the floor. Use vinegar-water rinse solution if alkaline cleaner is used.
4. Use only clean applicators, mops, pails, or pans for application.
5. For best results, use a lamb's wool applicator, cotton or saran mop.
6. Apply a thin, even coat—avoid puddles.
7. Extremely porous floors may require a second application of the sealer.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** May cause eye and skin irritation. Avoid contact with eyes and prolonged contact with skin. Wash thoroughly after handling. Do not take internally.

FIRST AID: EYES: In case of contact with eyes, flush immediately with plenty of water for at least 15 minutes. **SKIN:** Flush with plenty of water. Get medical attention if irritation persists. Wash contaminated clothing before reuse.

Before using this product read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.

FACTS

1. Seals and protects
2. Easy to apply
3. Improves beauty
4. Economical

BENEFITS

1. Floors are easier to clean and maintain, helps resist wear on finish coating and is the perfect foundation for finish coating of wax or polymers
2. Just mop on—it is self-leveling
3. The natural beauty and rich colors of flooring are brought out by first sealing with 3375
4. Cuts maintenance time and cost. High solids content means more square feet per gallon