



**3376**

# KLEER SEAL

**SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947**



**Year Round Protection For All Concrete Floors**

- **Dries For Traffic In 2 To 4 Hours**
- **Seals Against Penetrations Of Oil, Soil, Grease, Dirt, Stains**
- **Stops Surface Deterioration**
- **Floors Are Much Easier To Clean And Maintain**
- **Converts Dull Concrete To A Glossy, Attractive Finish**
- **Water Based, Non-Flammable No Solvent Odors**

**ALL CONCRETE FLOORS** should be sealed if they are expected to provide the maximum in performance and good looks. Use Foremost 3376 Kleer Seal to seal and preserve floors to insure a beautiful, long wearing surface. It is also a superb product for use on composition tile (asphalt, vinyl, rubber, linoleum, cork) and terrazzo floors.

**KLEER SEAL** is a fast-drying penetrating sealer with excellent durability and adhesion properties. This unique sealer dries to the touch in one hour and possesses no solvent odor like ordinary seals.

**IMPROVED APPEARANCE** — Kleer Seal dries to a clear, attractive surface. If desired, a second coat will produce an even higher gloss. It may also be applied over existing seals, paints or finishes.

**NOTE: DO NOT APPLY TO NEWLY PAINTED FLOORS.** Paint must be allowed to cure completely prior to application of FM 3376.

**STOPS DETERIORATION**—Unsealed floors are perpetually abrading. Proof? Simply sweep a small area—as long as you sweep, you will continue to create cement dust, indefinitely.

**ECONOMICAL**— A one coat sealer that provides long life protection. Worn traffic lanes can be easily spot-treated—new and old coats blend well.

## **NOTE**

Concrete floors are thought of as practically indestructible, and are often overlooked.

They can be attractive, and proper maintenance can vastly improve their appearance, increase durability and prevent them from becoming an eyesore.

Foremost 3376 helps provide this distinct advantage.

**RECOMMENDED FOR CONCRETE FLOORS IN EXCESS OF 3 MONTHS OLD**

**Packed In 55 Gallon Drums**

Rev. 11-5-15

Toll Free: 800-238-5150  
Local: 901-363-4340  
Fax: 901-375-3600

**Delta Foremost Chemical Corp.**  
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:  
[www.deltaforemost.com](http://www.deltaforemost.com)





# TECHNICAL DATA

## FOREMOST 3376 KLEER SEAL

Rev. 5-26-17

**DESCRIPTION:** A quality product designed for concrete floors in excess of 3 months old. It prevents dusting, staining and deterioration and is fast drying with excellent alkali resistance.

**APPLICATION:** This product is recommended as a sealer for concrete floors, composition tile (asphalt, vinyl, rubber, linoleum, cork) and terrazzo floors. It is a one coat sealer, although multiple coats may be applied for high gloss. It is especially resistant to alkali and finds widespread use throughout industry and institutions. It will prevent dusting and disintegration of the surface due to chemical change within the floor.

Typical Coverage: 350 square feet per gallon depending on method of application.

**DIRECTIONS:** The following application procedure should be followed for best results:

1. The floor should be thoroughly cleaned to remove all loose dust, soil, wax, grease, oil and other foreign matter, including old sealers. If necessary, a heavy duty concrete cleaner or alkaline solution should be used for this purpose. If this type of cleaning is used, then the floor must be rinsed several times and allowed to dry overnight.
2. A thin, even coat of Foremost 3376 Kleer Seal should be applied at a rate of one gallon per 350 square feet with a lamb's wool applicator or other suitable device.
3. The sealer will dry to the touch within one hour and traffic can resume within 2 to 4 hours.
4. When the sealer shows signs of wearing in traffic lanes, around machinery, in doorways, etc., those areas can be touched up by thoroughly cleaning the worn areas and applying Kleer Seal.
5. Remove with FM 3090 Wax Stripper. Applicators may be cleaned with water.

**NOTE:** DO NOT APPLY TO NEWLY PAINTED FLOORS. Paint must be allowed to cure completely prior to application of FM 3376.

**PRECAUTIONS:** **KEEP OUT OF REACH OF CHILDREN.** May cause eye and skin irritation. Avoid contact with eyes and prolonged contact with skin. Wash thoroughly after handling. Do not take internally.

**FIRST AID: EYES:** In case of contact with eyes, flush immediately with plenty of water for at least 15 minutes. **SKIN:** Flush with plenty of water. Get medical attention if irritation persists. Wash contaminated clothing before reuse.

Before using this product read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.

### FACTS

1. Fast drying
2. Easy to apply
3. Water based
4. Self-adhering
5. It's a penetrating sealer
6. Excellent for old floors

### BENEFITS

1. Dries to touch within one hour. Traffic may resume within 2 to 4 hours; no down time
2. Use conventional lamb's wool applicator or mop; applicators may be cleaned with water
3. No offensive odor
4. Touch-up wear spots without stripping
5. It penetrates into the concrete, bonding off moisture and preventing dusting. Makes floors easier to keep clean. Keeps merchandise and machinery more dust free
6. The natural beauty and rich colors of flooring are brought out by sealing with Foremost 3376 Kleer Seal