





SPECIALTIES FOR MAINTENANCE & SANITATION SINCE 1947

LUMBER BRITE

FM 4525B

- BRIGHTENS FADED WOOD STOCK
- CONCENTRATED
- FAST ACTING
- INDUSTRIAL STRENGTH

RECOMMENDED FOR

- LUMBER YARDS
- OUTDOOR WOOD FENCING
- WOOD DECKING
- GRAY AND MOLDED LUMBER

ECONOMICAL — May be diluted or applied as concentrate for instant results.

INCREASE PROFITS — Turns discolored, graying stock into desirable, saleable inventory.

EASY TO APPLY — Simply apply with a pump up sprayer.

INSTANT RESULTS — Watch faded stock brighten to brand-new wood grain immediately.

PRECAUTION — Highly corrosive, will bleach fabrics. Always test in an inconspicuous area first. Rinse after application.

PACKED IN 55 GALLON DRUMS











TECHNICAL DATA

FOREMOST 4525B LUMBER BRITE

Rev. 6-11-19

DESCRIPTION: Delta Foremost FM 4525B Lumber Brite is a concentrated, industrial-strength cleaner designed

to return discolored and faded wood to its new original appearance.

APPLICATION: For brightening faded, gray or molded wood stock. Recommended for use in lumber yards,

outdoor wood fencing, wood decking and any gray or molded lumber. Do not use on painted

or finished wood.

DIRECTIONS: Product may be applied as concentrate or diluted up to 5-10 times with water for economy. Fastest

results are seen when product is used at lower dilution levels. Apply with a pump-up sprayer.

Rinse after application.

PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. Highly Corrosive. May cause severe eye irritation.

Avoid contact with eyes and skin. Do not take internally.

FIRST AID: In case of contact, immediately flush eyes with large amounts of water until burning ceases. Get medical attention immediately if irritation persists. Skin: Wash with plenty of soap and water. Ingestion: Drink large quantities of milk or gelatin solution. If these are not available, drink large quantities of water. Do not give vinegar or other acids. Do not induce vomiting. Seek medical attention.

ENVIRONMENTAL HAZARD: This product is toxic to fish. Do not discharge into lakes, streams, ponds or public waterways unless in accordance with a NPDES permit.

PHYSICAL OR CHEMICAL HAZARDS: STRONG OXIDIZING AGENT. Mix only with water according to label directions. Mixing this product with chemicals (ammonia, acids, detergents, etc) will release chlorine gas which is irritating to eyes, lungs and mucous membranes.

Before using this product read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.