



529-ES WINTER-SLIX

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

PROTECTS EQUIPMENT AGAINST RUSTING WHEN NOT IN USE



Prevents Chain Lock-Up



Plow Blades Stay Free Of Caked Snow

KEEPS SALT / SAND MIXTURES FROM CLOGGING IN DE-ICING SPREADERS

FOREMOST 529-ES WINTER-SLIX keeps salt/sand mixtures from clogging in de-icing spreaders. Deliver a complete load without clogging spreaders. Slush from roads can get thrown into the beds of dump trucks causing salt and sand mixtures to clump or stick in truck beds.

PLOW BLADES STAY FREE OF CAKED SNOW. Keep down time to a minimum. Drivers don't have to Stop - Get Out - Kick or Knock caked snow from plow blades.

EFFECTIVE AT TEMPERATURES TO -40°F Never quits working regardless of temperature or snowfall.

RECOMMENDED FOR —
MUNICIPAL / STATE / PRIVATE SNOW CONTROL/
REMOVAL OPERATIONS

Packed in 55 Gallon Drums

Rev. 11-17-14

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com





TECHNICAL DATA

FOREMOST 529-ES WINTER-SLIX

Rev. 12-11-15

DESCRIPTION: A special silicone fluid which deposits a long lasting film to serve as a lubricant, release agent, anti-sticking agent and protective coating. The film is heat stable from -40°F to 600°F.

APPLICATION: Use as a release agent for ice/snow removal equipment, snow plows and salt spreaders. Prevents caking of salt/sand mixtures due to slush being thrown into beds of trucks and equipment. Keeps drive chains on spreaders from being clogged with salt. Prevents snow from caking on blades of snowplows. Protects equipment from rusting when not in use.

Also ideal for concrete release. Use on ready mix trucks to prevent cement dust from bonding. Also excellent form release for concrete forms and working tools.

DIRECTIONS: Use as supplied in any good spray equipment. Spray a fine mist of Foremost 529-ES Winter-Slix into beds of dump trucks, salt spreaders, or onto blades of snow plows. Apply liberally to Urethane snowblade plow tips to condition and reduce embrittlement. Reapply as needed.

Always apply to clean surfaces. Wipe off excess with clean cloth. Use sparingly. A thin film is sufficient; then re-coat as needed. Do not apply to high temperature surfaces.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** Contains Petroleum Distillate. Do not take internally. **MAY BE HARMFUL OR FATAL IF SWALLOWED.** Keep away from heat and open flame. Use with adequate ventilation. Avoid breathing of spray mist. Avoid contact with skin and eyes. If ingested, get immediate medical attention. Keep container closed when not in use. Prolonged contact with skin can cause moderate irritation, defatting, dermatitis.

FIRST AID: If on SKIN: Wash thoroughly with soap or mild detergent and water. **If in EYES:** Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention. **INGESTION:** Get immediate medical attention.

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.