



585 SOLVENT CLEANER

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947



Low toxicity, nonflammable and no flash point.

PROTECTS — Does not contain 1,1,1-Trichloroethane or CFC's.

NONCORROSIVE — No oxidation or rusting as with water soluble products. Nonconductive — Self-evaporative. Leaves physically clean surfaces, no oily films.

FAST — Spray or wipe on; then air blast, wipe, or simply allow to air dry.

VERSATILE — A must for every industrial plant. Does not contain flammable petroleum solvents.

ECONOMICAL — Saves labor time and material cost. Foremost 585 Solvent Cleaner is 100% active. Light applications do heavy cleaning.

Packaged in 55 Gallon Drums.

CLEANS

**Grease, Grime, Tars,
Waxes And Oils From
Electrical Equipment
And Other Precision
Metal Surfaces.**

UNEXCELLED FOR SUCH VARIED APPLICATIONS AS CLEANING:

- Industrial motors and generators
- Cartoning machinery in dairies
- Drills, lathes and presses
- Control panels, coils, windings and switches
- Packaging machines in potato chippers
- Removing protective (rust preventative) coatings
- Diesel electric traction motors

ALSO AVAILABLE IN CONVENIENT AEROSOLS

Excellent removal of grease, grime, oil, and heavy soils. Leaves no residue — no rinse needed — safe from fire hazards. Net Contents 18 oz.



12 Doz. or 3/48 cases	8 Doz. or 2/48 cases	4 Doz. or 1/48 cases
-----------------------------	----------------------------	----------------------------

Rev. 9-12-13

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com



TECHNICAL DATA

FOREMOST 585 SOLVENT CLEANER

Rev. 2-16-17

DESCRIPTION: A versatile, cold safety solvent developed especially to replace the use of dangerous solvents and to be consistent with the requirements of safety and insurance departments. It does not contain 1,1,1-Trichloroethane or CFC's. Foremost 585 Solvent Cleaner does not contain flammable petroleum solvents.

This formulation rapidly and effectively removes oil, dirt, grease, grime, wax, lint, carbon dust, metallic particles and gum from all metal surfaces and other areas specified in directions. It exhibits no true flash point. This water-white and noncorrosive solvent dries quickly but not too fast to clean effectively. Treatment with it leaves no oily residue to impair paint adhesion or damage motors or other electrical equipment, and is safe for all metal, wood surfaces, sound paint and insulating varnish.

APPLICATION: Designed for maintenance of equipment such as diesel electric traction motors, generators, industrial motors, coils, windings, switches, control panels, rheostats, stationary machinery, etc. Also, safely removes solvent based waxes from hardwood flooring without leaving undesirable residual films and odors.

DIRECTIONS: **General Cleaning:**

1. Turn off all electrical equipment before cleaning.
2. Spray Foremost 585 Solvent Cleaner on the surfaces using a heavy wet spray pattern.
A second application may be necessary for more stubborn soils.
3. Flush rinse with a second application.
4. Dry off with air blast, wiping, or allow to air dry.

Vat Cleaning:

1. Fill the vat with Foremost 585 Solvent Cleaner.
2. Immerse articles to be cleaned in the cleaner.
3. Let soak for a few minutes.
4. Remove the articles from the vat and dry by means of an air blast or allow to air dry.

NOTE: DO NOT ATTEMPT TO CLEAN ELECTRICAL EQUIPMENT WHILE IN USE.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** Contains chlorinated solvents. Vapor harmful. Use only with adequate ventilation. Avoid prolonged or repeated breathing of vapor. High vapor concentrations can cause dizziness, unconsciousness or death. Ventilation must be sufficient to limit exposure below 50 ppm TWA. **DO NOT TAKE INTERNALLY.** Swallowing can cause injury, illness or death. **Avoid prolonged or repeated contact with skin.** Contact can cause skin irritation and dermatitis. Do not get in eyes. Will cause discomfort and irritation. Do not eat, drink or smoke in work area.

FIRST AID: EYES: Flush eyes thoroughly with large amounts of water. If irritation persists, see a physician. **SKIN:** Remove contaminated clothing and shoes. Wash skin with warm water and soap. Wash clothes and air out shoes. **INGESTION:** Seek medical attention immediately. Do not induce vomiting. **INHALATION:** Remove patient to fresh air. If breathing stops, give artificial respiration. Call a physician. **NOTE TO PHYSICIAN:** Avoid use of adrenaline in any case where a person has been over come by trichloroethylene.

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.