

## SAFETY DATA SHEET

Revision Date 28-May-2015

Version 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier** 

Product Name Foremost 599-ES Deo Mist Aerosol

UN1950

**UN/ID No** 

Product Code 599-ES

Recommended Use of the Chemical and Restrictions on Use

**Recommended Use** Air Freshener.

**Details of the Supplier of the Safety Data Sheet** 

**Supplier Address** 

Delta Foremost Chemical Corporation 3915 Air Park St.

Memphis, Tennessee 38118

**Emergency Telephone Number** 

Company Phone Number (901) 363-4340

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

## Classification

Serious Eye Damage/Eye Irritation	Category 2A
Flammable Aerosols	Category 1
Specific Target Organ Toxicity – Single Exposure	Category 3

# Signal Word DANGER

## **Hazard Statements**

Causes serious eye irritation Extremely flammable aerosol May cause drowsiness or dizziness



Appearance Clear, colorless liquid

Physical State Liquid

**Odor** Pleasant

Revision Date 28-May-2015

#### **Precautionary Statements - Prevention**

Use personal protective equipment as required

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Do not spray on an open flame or other ignition source

Pressurized container. Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 122°F.

Avoid breathing mist or vapor.

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Get medical attention if irritation occurs

IF ON SKIN: Wash with plenty of soap and water

If skin irritation persists: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

## **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50°C.

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Hazards Not Otherwise Classified (HNOC)**

May be harmful if swallowed

#### **Other Hazards**

None.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Acetone	67-64-1	Proprietary
Butane	106-97-8	Proprietary
Propane	74-98-6	Proprietary

Product contains a proprietary mixture of ingredients.

## 4. FIRST AID MEASURES

## First Aid Measures

General Advice If exposed or concerned: Get medical advice/attention. Provide this SDS to medical

personnel for treatment.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation occurs.

Foremost 599-ES Deo Mist Aerosol

Revision Date 28-May-2015

**Skin Contact** Flush with water while removing contaminated clothing and shoes before reuse. If irritation

persists, get medical attention.

Inhalation Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial

respiration if not breathing. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Do NOT induce vomiting. Seek medical attention immediately.

#### Most Important Symptoms and Effects, both Acute and Delayed

Symptoms Liquid in eyes can cause pain and irritation. Corneal injury likely. May cause skin and eye

irritation. Ingestion may result in irritation of mouth and gastrointestinal tract. Vomiting may cause chemical pneumonia. Overexposure by inhalation can cause irritation of the respiratory tract and adverse effects on the central nervous system. High concentrations or

prolonged exposure can cause unconsciousness and death.

## Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

## Suitable Extinguishing Media

Dry chemical, foam, or carbon dioxide.

Unsuitable Extinguishing Media Not determined.

#### **Specific Hazards Arising from the Chemical**

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact

with skin and eyes and inhalation of vapors.

#### Methods and Material for Containment and Cleaning Up

Methods for Containment Prevent further leakage or spillage if safe to do so. Absorb liquid with sawdust, sand or

industrial absorbent.

Methods for Cleaning Up Sweep up absorbed material and shovel into suitable containers for disposal. Discard any

product, residue, disposable container or liner in full compliance with federal, state, and

local regulations. For waste disposal, see section 13 of the SDS.

\_\_\_\_\_

#### 7. HANDLING AND STORAGE

#### **Precautions for Safe Handling**

Advice on Safe Handling

Pressurized container. Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dray. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Ground and bond containers when transferring material. Do not re-use empty containers. Avoid contact with skin, eyes or clothing. Avoid breathing vapors. Avoid breathing mists. Use only in well-ventilated areas. Avoid prolonged exposure. Observe good industrial hygiene practices.

#### Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Keep in

properly labeled containers. Store locked up.

Incompatible Materials Oxidizing agents.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	_
		(vacated) STEL: 2400 mg/m <sup>3</sup>	
		The acetone STEL does not apply	
		to the cellulose acetate fiber	
		industry. It is in effect for all other	
		sectors	
		(vacated) STEL: 1000 ppm	
Butane	STEL: 1,000 ppm	-	TWA: 800 ppm
106-97-8			TWA: 1,900 mg/m <sup>3</sup>
Propane	-	TWA: 1,000 ppm	TWA: 1,000 ppm
74-98-6		TWA: 1,800 mg/m <sup>3</sup>	TWA: 1,800 mg/m <sup>3</sup>

## **Appropriate Engineering Controls**

Engineering Controls Ventilation must be adequate to maintain the ambient workplace atmosphere below the

exposure limit(s) outlined in the SDS.

#### Individual Protection Measures, such as Personal Protective Equipment

**Eye/Face Protection** Goggles or face shield.

**Skin and Body Protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact. Wear protective Neoprene™ gloves, Rubber

gloves.

**Respiratory Protection**Use self-contained breathing apparatus if there is a heavy vapor about 300 ppm.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands after

use and wash contaminated clothes before reuse.

\_\_\_\_\_

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on Basic Physical and Chemical Properties

Physical State Liquid / aerosol Appearance Clear liquid

AppearanceClear liquidOdorPleasantColorColorlessOdor ThresholdNot determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

PH Not determined
Melting Point/Freezing Point Not determined

**Boiling Point/Boiling Range** 82°F

Flash Point Not determined

Evaporation Rate >1

Flammability (Solid, Gas) Not determined

Upper Flammability Limits 9.5% Lower Flammability Limit 1.9%

Vapor PressureNot determinedVapor DensityNot determined

Specific Gravity 0.810

Water Solubility Soluble in water Solubility in Other Solvents Not determined **Partition Coefficient** Not determined **Autoignition Temperature** Not determined **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

## 10. STABILITY AND REACTIVITY

(1=Water)

#### Reactivity

Not reactive under normal conditions.

#### **Chemical Stability**

Stable under recommended storage conditions.

## **Possibility of Hazardous Reactions**

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

#### **Conditions to Avoid**

Avoid heat, sparks, open flames and other ignition sources.

## **Incompatible Materials**

Acids, oxidizing agents.

## **Hazardous Decomposition Products**

No hazardous decomposition products are known.

## 11. TOXICOLOGICAL INFORMATION

#### **Information on Likely Routes of Exposure**

**Product Information** 

**Eye Contact** Causes serious eye irritation.

.....

**Skin Contact** No irritation expected.

**Inhalation** Prolonged inhalation may be harmful.

**Ingestion** Expected to be a low ingestion hazard.

## **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone = 5800 mg/kg ( Rat ) 67-64-1		-	-
Butane 106-97-8	= 1,658 mg/kg (Rat)	-	= 1,355 mg/L (Rat) 2 h
Propane 74-98-6	-	-	= 1,237 mg/L ( Mouse ) 120 min = 1,355 mg/L ( Rat ) 4 h

#### Information on Physical, Chemical and Toxicological Effects

**Symptoms** Please see section 4 of this SDS for symptoms.

## Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Germ Cell Mutagenicity None.

Carcinogenicity None.

**STOT - Single Exposure** May cause drowsiness or dizziness.

**Chronic Toxicity** Prolonged inhalation may be harmful.

Aspiration Hazard Not likely.

## **Numerical Measures of Toxicity**

Not determined

## 12. ECOLOGICAL INFORMATION

## **Ecotoxicity**

Toxic to aquatic life with long lasting effects.

## **Component Information**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Acetone		4.74 - 6.33: 96 h	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia
67-64-1		Oncorhynchus mykiss mL/L	_	magna mg/L EC50 Static
		LC50 6210 - 8120: 96 h		12600 - 12700: 48 h Daphnia
		Pimephales promelas mg/L		magna mg/L EC50
		LC50 static 8300: 96 h		
		Lepomis macrochirus mg/L		
		I C50		

## **Persistence and Degradability**

Not determined.

#### **Bioaccumulation**

Not determined

#### **Mobility**

Chemical Name	Partition Coefficient
Acetone	-0.24
67-64-1	
Butane	2.89
106-97-8	
Propane	2.36
74-98-6	

#### **Other Adverse Effects**

Not determined

## 13. DISPOSAL CONSIDERATIONS

## **Waste Treatment Methods**

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations. Do not puncture, incinerate, or crush.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations. Do not puncture, incinerate, or crush.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

## 14. TRANSPORT INFORMATION

**Note** Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

<u>DOT</u>

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Packing Group N/A

<u>IATA</u>

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Packing Group N/A

**IMDG** 

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Packing Group N/A

## 15. REGULATORY INFORMATION

#### **International Inventories**

Not Determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

#### **US Federal Regulations**

#### **CERCLA**

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

#### **SARA 313**

Not determined.

## **CAA (Clean Air Act)**

Butane, CAS No. 106-97-8 Propane, CAS No. 74-98-6

#### **US State Regulations**

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Acetone	X	X	X
67-64-1			
Butane	X	X	X
106-97-8			
Propane	X	X	X
74-98-6			

# 16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	1	4	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	4	0	Not determined

Revision Date 28-May-2015 Revision Note 28-May-2015

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

.....