



SUPER TRANSPO WASH PREP POWER

A REVOLUTIONARY BREAKTHROUGH
IN VEHICLE WASHING!

COMMERCIAL | INDUSTRIAL | FLEET



Delta Foremost Chemical Corp.

3915 AIR PARK STREET • MEMPHIS, TENNESSEE 38118

FM 615-ES

SUPER TRANSPO WASH

FM 615B-ES

PREP POWER

USE ONE PRODUCT TO CLEAN
TRACTORS, TRAILERS, WHEELS,
ENGINES, CHASSIS, CHROME,
WINDSHIELDS AND GRILLES.



DELTA FOREMOST PRESENTS

Cutting-edge road film removing technology; fast, efficient, multipurpose cleaning for auto detail & vehicle washing. Power spray on and rinse off. No time-consuming wiping, brushing or mitting required.

CLEANS AND BRIGHTENS

Perfect for painted and aluminum wheels. Not for use on "chrome finished" aftermarket aluminum. Use at weakest effective concentration on aluminum that has been previously exposed to alkaline or acidic cleaners and brighteners.

VERSATILE USAGE

May be used with a hot or cold pressure washer. Heated pressure washing provides the quickest, most thorough results. Unique surfactant technology breaks the bond of tough road film - preventing streaking and leaving glass film free.

ECONOMICAL

A single drum of highly concentrated Super Transpo Wash will make 4-5 drums of soap using the FM 9602 Meter Mite. These drums may then be connected to a pressure washer and diluted again through the washer's soap valve. 1-2 ounces of FM 615-ES Super Transpo Wash at the tip of the wand provides excellent cleaning performance. Wet the vehicle down with dilute solution and allow a couple of minutes of presoak time to further enhance performance.





• REMOVES TOUGH SOILS FROM ENGINES



• REMOVES BUGS



• CUTS THROUGH TOUGH ROAD FILM



• RINSE AWAY BRAKE DUST

EASY TO MANAGE

Concentrated liquid easily dilutes and adapts perfectly to any automatic mixing and dispensing system. No clumpy powder to dissolve and stir. Injects directly into the water line from the drum.

ECONOMICAL LABOR SAVER

FM 615-ES is concentrated, saving you big money by allowing you to add your own water. Since it requires no brushing, you also save labor and man-hours. Wash multiple trucks in the time it used to take to wash just one and skyrocket your productivity.

SAFE ON ALL SURFACES

Leaves surfaces gleaming with a "like new" luster. Absolutely safe on any material found on a vehicle:

Aluminum | Iron | Steel | Stainless Steel | Glass
Rubber | Plastic | Zinc | Chromium | Cadmium

When used according to directions, it will not damage, degloss or streak sound paint. It will not attack decals or painted signs.

- Removes brake dust from O.E.M. Aluminum and clear coat wheels
- Cleans and brightens white wall tires
- Removes tough soil and grease from rocker panels, drive components and engines
- Easily removes bugs with pre-spray and pressure rinse

NOTE: NOT FOR USE ON POLISHED OR AFTERMARKET ALUMINUM.

PACKED IN 55 GALLON DRUMS



TECHNICAL DATA | FM 615 / 615B-ES

DESCRIPTION A highly concentrated product for fast and efficient removal of road film, oil, grease, brake dust and dirt deposits from all types of industrial and automotive equipment. FM 615 / 615B-ES Super Transpo Wash is very economical, easy to use, and has no unpleasant residual odors. This compound is safe on aluminum, iron, chrome, steel, glass, zinc, magnesium, plastics, rubber, etc. It cleans quickly and thoroughly and is noncorrosive to metal or painted surfaces. It performs through combined chemical and physical action by penetrating, emulsifying, wetting and water softening.

NOTE: Not for use on polished or aftermarket aluminum.

APPLICATION Recommended for use through all types of spray or dispensing equipment at the highest pressures normally available. Higher pressures generally give better performance, especially on stubborn soils. Super Transpo Wash and Prep Power are recommended for all types of automotive, and truck finishes.

DIRECTIONS: VEHICLE WASHING (NOTE: Avoid washing vehicle in direct sun)

FOR PRESSURE SPRAY APPLICATION:

- 1) Adjust chemical metering valve to dilute chemical at approximately 80:1 to 100:1. To control waste, this can be accomplished by pre-diluting FM 615-ES or 615B using a Meter Mite or Magnetic Injector set at 4:1, then opening the chemical metering valve approximately 1 to 1-1/2 turns.
- 2) Spray solution onto vehicle for a fast wet-down. Holding spray nozzle 1-2 feet from vehicle's surface, cover entire vehicle thoroughly.
- 3) Apply Super Transpo Wash with the pressure nozzle about 12 to 18 inches from the vehicle surface, working from the bottom of the vehicle up. Allow 1 to 3 minutes contact time in most situations.
- 4) Rinse vehicle from the top down, starting at the same point as with soap application (This provides even contact time for entire vehicle).
- 5) A second application or agitation with a brush or swab may be necessary in heavily soiled areas such as greasy handprints and heavily sooted sections.

FOR MANUAL USE

- 1) Predilute FM 615-ES and 615B into a bucket at between 40-100:1 with water.
- 2) Apply with soft bristle truck wash brush massaging all surfaces. Avoid direct contact with skin (wear rubber gloves).
- 3) Rinse with clear water until sudsing is no longer evident.

REMOVAL OF BRAKE DUST, DEGREASING ENGINES AND BUG REMOVAL

FOR PRESSURE SPRAY METHOD

- 1) Dilute Foremost 615-ES and 615B between 4-10:1 with water.
- 2) Prespray wheels and tires and allow to remain on surface 1-2 minutes. Do not allow to dry on surface.
- 3) Pressure rinse - no brushing is necessary.

FOR MANUAL USE

- 1) Dilute FM 615-ES and 615B between 10-15:1 with water.
- 2) Apply with soft bristle brush massaging all surfaces. Avoid direct contact with skin (wear rubber gloves).
- 3) Rinse with clear water until sudsing is no longer evident.

PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN: May cause eye irritation. Avoid contact with eyes. Do not take internally. May be harmful if swallowed. **FIRST AID:** In case of contact, immediately flush with water for at least 15 minutes. Get medical attention if irritation persists.

Rev. 10-2-18



Contact Us



t 1.800.238.5150
f 1.901.375.3600



sales@deltaforemost.com
deltaforemost.com



3915 Air Park Street
Memphis, TN 38118