



## FM 615B-ES PREP POWER

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

### *Fast, Efficient Multi-Purpose Cleaning for Automotive Detail and Vehicle Washing*



Power Spray Vehicle Washing



Wheels



Engine Degreasing



Bug Removal—Pre-Wash

- Removes brake dust from O.E.M. Aluminum and clear coat wheels
- Cleans and brightens white wall tires
- Removes tough soils and grease from rocker panels, drive components and engines
- Easily removes bugs with prespray and pressure rinse

#### RECOMMENDED FOR —

- New and used car get-ready
- Touchless and tunnel car washes
- Rental car fleets
- Auto detail operations

#### • EASY TO MANAGE AND WORK WITH —

concentrated liquid easily dilutes and adapts perfectly to any automatic mixing and dispensing system. No clumpy powder to dissolve and stir. Injects directly into the water line from the drum.

#### • ECONOMICAL LABOR SAVER —

since **Prep Power** is concentrated, you save big money by adding your own water. Since it requires no brushing, you save numerous man-hours. You can now wash many cars and trucks in the time it used to take to wash just one and skyrocket your productivity.

#### • SAFE ON ALL SURFACES —

Leaves them all gleaming with a "like new" luster. Absolutely safe on any material found on a vehicle when used according to directions:

Aluminum • Iron • Steel • Stainless Steel  
Painted Surfaces • Glass • Rubber • Zinc  
Plastic • Chromium • Cadmium

When used according to directions, it will not damage, degloss or streak sound paint. It will not attack decals or painted signs. **Not for use on aftermarket polished aluminum.**

PACKED in 55 Gallon Drums

Rev. 6-3-14

Toll Free: 800-238-5150  
Local: 901-363-4340  
Fax: 901-375-3600

**Delta Foremost Chemical Corp.**  
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:  
[www.deltaforemost.com](http://www.deltaforemost.com)





# TECHNICAL DATA

## FOREMOST 615B-ES PREP POWER

Rev. 06-28-11

**DESCRIPTION:** A highly concentrated alkaline product for fast and efficient removal of road film, oil, grease, brake dust and dirt deposits from all types of industrial and automotive equipment. FM 615B-ES Prep Power is very economical, easy to use, and has no unpleasant residual odors. This compound is safe on aluminum, iron, chrome, steel, glass, zinc, magnesium, plastics, rubber, etc. when used according to directions. It cleans quickly and thoroughly and is noncorrosive to metal or painted surfaces. It performs through combined chemical and physical action by penetrating, emulsifying, wetting and water softening.

**APPLICATION:** Recommended for use through all types of spray or dispensing equipment at the highest pressures normally available. Higher pressures generally give better performance, especially on stubborn soils. Prep Power is recommended for all types of automotive finishes.

**DIRECTIONS:** **VEHICLE WASHING** (NOTE: Avoid washing vehicle in direct sun. Prewet all surfaces before applying FM-615B-ES.)

### **FOR PRESSURE SPRAY APPLICATION:**

- 1) Adjust chemical metering valve to dilute chemical at approximately 80:1 to 100:1.
- 2) Spray solution onto vehicle for a fast wet-down. Hold spray nozzle 1-2 feet from vehicle's surface, working from the bottom of the vehicle up, covering entire vehicle thoroughly. Allow 1 to 3 minutes contact time in most situations.
- 3) Rinse vehicle from the top down, starting at the same point as with soap application (This provides even contact time for entire vehicle).

### **FOR MANUAL USE**

- 1) Predilute 1 part FM 615B-ES into a bucket with between 40 and 100 parts water.
- 2) Apply with soft bristle truck wash brush massaging all surfaces. Avoid direct contact with skin (wear rubber gloves).
- 3) Rinse with clear water until sudsing is no longer evident.

### **FOR REMOVAL OF BRAKE DUST AND DEGREASING ENGINES**

#### **FOR PRESSURE SPRAY METHOD**

- 1) Dilute 1 part Foremost 615B-ES with between 4 and 10 parts water.
- 2) Prespray wheels and tires and allow to remain on surface 1-2 minutes. Do not allow to dry on surface.
- 3) Pressure rinse - no brushing is necessary.

#### **FOR MANUAL USE**

- 1) Dilute 1 part FM 615B-ES with between 10 and 15 parts water.
- 2) Apply with soft bristle brush massaging all surfaces. Avoid direct contact with skin (wear rubber gloves).
- 3) Rinse with clear water until sudsing is no longer evident.

### **FOR BUG REMOVAL AND ROCKER PANEL CLEANING**

- 1) Dilute 1 part FM 615B-ES with between 10 and 15 parts water.
- 2) Spray only onto surfaces with bug stains.
- 3) Allow 1-2 minutes contact time. Pressure rinse. Do not allow to dry on surface. (Avoid use on polished aluminum truck grills and bumpers.)

**PRECAUTIONS:** **KEEP OUT OF REACH OF CHILDREN:** May cause eye irritation. Avoid contact with eyes. Do not take internally. May be harmful if swallowed. **FIRST AID:** In case of contact, immediately flush with water for at least 15 minutes. Get medical attention if irritation persists.