



FM 618-ES POWER WASH

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

VEHICLE WASHING, BRAKE DUST REMOVAL, BUG REMOVAL AND DEGREASING IN ONE POWER PACKED PRODUCT!



BREAKS FILM WITHOUT BRUSHING

- **ECONOMICAL**

FM 618-ES Power Wash is concentrated for economy, providing cost effective ready to use solutions.

- **VERSATILE**

One product provides multiple applications.

- **REDUCE LABOR COST**

Touch-free washing eliminates labor intensive brushing and mitting.

- **SAFE ON ALL SURFACES**

Leaves them all gleaming with a "like new" luster. Absolutely safe on any material found on a vehicle:

Aluminum • Iron • Steel
Stainless Steel • Glass • Rubber
Plastic • Zinc • Chromium
Cadmium

When used according to directions, it will not damage, degloss or streak sound paint. It will not attack decals or painted signs. **NOTE: Not for use on polished or after-market aluminum.**



BUG REMOVAL - PRE WASH



ENGINE DEGREASING



BEFORE | AFTER

PACKED in 55 Gallon Drums



HANDS FREE WASHING

- Removes brake dust from O.E.M. Aluminum and clear coat wheels
- Cleans and brightens white wall tires
- Removes tough soils and grease from rocker panels, drive components and engines
- Easily removes bugs with prespray and pressure rinse
- Non-Acid

RECOMMENDED FOR

- New and used car preparation
- Heavy Equipment Dealers
- Rental car fleets
- Auto detail operations
- Equipment Rental companies
- Trucking Firms

Rev. 11-13-14

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com





TECHNICAL DATA

FOREMOST 618-ES POWER WASH

Rev. 02-27-12

DESCRIPTION: A highly concentrated product for fast and efficient removal of road film, oil, grease, brake dust and dirt deposits from all types of industrial and automotive equipment. FM 618-ES Power Wash is very economical, easy to use, and has no unpleasant residual odors. This compound is safe on aluminum, iron, chrome, steel, glass, zinc, magnesium, plastics, rubber, etc. It cleans quickly and thoroughly and is noncorrosive to metal or painted surfaces. It performs through combined chemical and physical action by penetrating, emulsifying, wetting and water softening.

NOTE: Not for use on polished or after-market aluminum.

APPLICATION: Recommended for use through all types of spray or dispensing equipment at the highest pressures normally available. Higher pressures generally give better performance, especially on stubborn soils. Power Wash is recommended for all types of automotive finishes.

DIRECTIONS: **VEHICLE WASHING** (NOTE: Avoid washing vehicle in direct sun.)

FOR PRESSURE SPRAY APPLICATION:

- 1) Adjust chemical metering valve to dilute chemical with approximately 1 part chemical to 20-25 parts water.
- 2) Apply Power Wash with the pressure nozzle about 12 to 18 inches from the vehicle surface, working from the bottom of the vehicle up. Allow 1 to 3 minutes contact time in most situations. Cover entire vehicle thoroughly.
- 3) Rinse vehicle from the top down, starting at the same point as with soap application (This provides even contact time for entire vehicle).
- 4) A second application or agitation with a brush or swab may be necessary in heavily soiled areas such as greasy handprints or heavily sooted sections.

FOR MANUAL USE

- 1) Dilute 1 part FM 618-ES into a bucket with approximately 10 to 24 parts water.
- 2) Apply with soft bristle truck wash brush massaging all surfaces. Avoid direct contact with skin (wear rubber gloves).
- 3) Rinse with clear water until sudsing is no longer evident.

REMOVAL OF BRAKE DUST AND DEGREASING ENGINES

FOR PRESSURE SPRAY METHOD

- 1) Dilute 1 part FM 618-ES with approximately 1 to 3 parts water.
- 2) Prespray wheels and tires and allow to remain on surface 1-2 minutes. Do not allow to dry on surface.
- 3) Pressure rinse - no brushing is necessary.

FOR MANUAL USE

- 1) Dilute 1 part FM 618-ES with approximately 3 to 4 parts water.
- 2) Apply with soft bristle brush massaging all surfaces. Avoid direct contact with skin (wear rubber gloves).
- 3) Rinse with clear water until sudsing is no longer evident.

FOR BUG REMOVAL AND ROCKER PANEL CLEANING

- 1) Dilute 1 part FM 618-ES with approximately 3 and 5 parts water.
- 2) Spray only onto surfaces with bug stains.
- 3) Allow 1-2 minutes contact time. Pressure rinse. Do not allow to dry on surface. (Avoid use on polished aluminum truck grills and bumpers.)

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN:** May cause eye irritation. Avoid contact with eyes. Do not take internally. May be harmful if swallowed. **FIRST AID:** In case of contact, immediately flush with water for at least 15 minutes. Get medical attention if irritation persists.