



631

SUPER STEAMER

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947



FM 631 Super Steamer works to clean even the heaviest contamination.

EXTRA POWER FOR GENERAL STEAMCLEANING

WHY DO THE JOB HALF-WAY, WHEN ALL-THE-WAY INVOLVES NOTHING MORE?

POWERFUL—Detergents, solvents, highly alkaline builders, wetting agents, all combined in one high strength liquid to produce the best cleaning results.

ECONOMICAL—Most general steamcleaning jobs can be completed with low concentrations of 631 Super Steamer. Heavier concentrations will clean practically any contamination.

VERSATILE—For iron, steel, copper and ferrous alloyed surfaces. Should not be used on aluminum or painted surfaces. May damage soft metals.

RECOMMENDED FOR —

- Equipment Shops
- Railroads
- Manufacturing Plants
- Bottlers
- Dairies
- Meat Packers
- Poultry and Related Food Processors

Authorized by USDA for use in federally inspected meat and poultry plants.

Packed in 55 Gallon Drums

Rev. 11-28-17

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com





TECHNICAL DATA

FOREMOST 631 SUPER STEAMER

Rev. 11-28-17

DESCRIPTION: A highly concentrated alkaline product designed for the fast and efficient removal of heavy deposits of grease, oil and dirt from equipment and machinery. It is recommended exclusively for use on iron, steel, copper and ferrous alloyed surfaces; it will attack soft metals such as aluminum, zinc, tin, galvanized, babbitt or bearing metal. This compound cleans quickly and thoroughly by the combined chemical and physical action of penetration, saponification and detergency.

APPLICATION: Recommended for use in all types of pressure steam generating equipment. It is suggested for heavy duty cleaning of farm equipment, road machinery, industry, food processors, institutions, automotive, building maintenance and restaurants. This product is extensively used in renovating operations involving automatic and industrial equipment.

DIRECTIONS: **HEAVY DUTY STEAMCLEANING:** Use 1 to 3 parts per 20 parts of water. Rinse with clean water after steamcleaning.

FOR POWER SPRAY OR STEAMCLEANING: Charge solution tank with one part of concentrate to 5 to 100 parts of water depending on severity of soiling. After cleaning, rinse with water or wet steam.

MANUAL: Dilute concentrate with 5 to 40 parts water depending on severity of soiling. After cleaning, rinse with water or wet steam.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** Contains potassium hydroxide, and ethylene glycol monobutyl ether. Causes severe burns to eyes and skin. Do not get in eyes, skin, or clothing. Do not take internally. Prolonged and/or repeated exposure may lead to redness, swelling, and irritation. Wash thoroughly after handling. When handling, always wear chemical splash goggles, face shield, rubber gloves and protective clothing.

FIRST AID: EYES AND SKIN: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. **INGESTION:** If swallowed do not induce vomiting. If person is conscious, give large quantities of water or milk, if available. Get medical attention immediately.

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.