



## 634-ES LIQUID SPRAY-CLEAN

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947



### DYNAMIC CLEANING POWER!

### METERS PRECISELY RINSES FREELY

Authorized by USDA for use in federally  
inspected meat and poultry plants.

## SUPREME PERFORMANCE IN LIQUID SPRAY WASHING

**SPECIALIZED FORMULATION** — Proven effective in hard surface cleaning. Built-in cleaning boosters and wetting agents combined to give superior performance in a spray car wash. Effective in hard and soft water.

**SUPERIOR DETERGENCY** — For units washed frequently, one spraying followed by rinse keeps vehicles showroom bright. Heavier soils and road film may require two applications. Heavy road film, grime or soil build-up may require brushing.

**EASILY ADAPTED** — To any automatic mixing and dispensing system. No powders to mix and pre-dissolve. Meters directly from drum.

#### NOTE

**FLAKES, POWDERS**, and other old-fashioned carwashing compounds deteriorate in storage.

Foremost 634, an easy to handle and simple to measure liquid, is not hygroscopic. It does not cake, stratify or lose effectiveness.

#### RECOMMENDED FOR:

Coin-Op car and truck washes,  
wand, brush and automatic  
Truck Lines  
Sanitation Equipment  
Service Stations  
Car Washes  
All Fleet Operations

**PACKED IN 55 GALLON DRUMS**

Rev. 5-17-16

Toll Free: 800-238-5150  
Local: 901-363-4340  
Fax: 901-375-3600

**Delta Foremost Chemical Corp.**  
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:  
[www.deltaforemost.com](http://www.deltaforemost.com)





# TECHNICAL DATA

## FOREMOST 634-ES LIQUID SPRAY-CLEAN

Rev. 5-17-16

**DESCRIPTION:** A highly concentrated product for fast and efficient removal of oil, grease, and dirt deposits from all types of industrial and automotive equipment. Foremost 634-ES Liquid Spray-Clean is very economical, easy-to-use, and has no unpleasant residual odors. This compound is safe on aluminum, iron, chromium, cadmium, lead, steel, zinc, magnesium, plastics, rubber, etc. It cleans quickly, thoroughly and is non-caustic and non-toxic. It performs through combined chemical and physical action by penetrating, emulsifying, saponifying, wetting and water softening.

**APPLICATION:** Recommended for use through all types of spray or dispensing equipment at the highest pressures normally available. Higher pressures generally give better performance, especially on stubborn soils. It is recommended for all types of automotive finishes, especially those requiring maximum protection.

**DIRECTIONS:** **NOTE:** Avoid washing vehicle in direct sun.

1. Mix approximately 1 quart of concentrate in 50 gallons of water. (Warm water will improve results.)
2. Spray solution onto vehicle for fast wet-down, holding spray nozzle 1-2 feet from vehicle's surface.
3. Holding spray nozzle 8-12 inches from the surface, cover the entire vehicle thoroughly. Brush or swab if heavy soil or road film is present.
4. Rinse with plain water.

**PRECAUTIONS:** **KEEP OUT OF REACH OF CHILDREN.** Contains potassium hydroxide. May cause eye irritation. Avoid contact with skin, eyes and clothing. No irritation is likely following short contact periods with human skin. Prolonged and/or repeated exposure may lead to redness, swelling or irritation. Do not take internally.

**FIRST AID: EYES:** In case of contact, immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately. **SKIN:** In case of contact, immediately flush eyes with plenty of water.

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.