

SAFETY DATA SHEET

Revision Date 5-March-2019

Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name Foremost 642-ES Bling Premium Polish Aerosol

UN1950

UN/ID No

Product Code 642-ES

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Metal Polish

Details of the Supplier of the Safety Data Sheet

Supplier Address

Delta Foremost Chemical Corporation

3915 Air Park St.

Memphis, Tennessee 38118

Emergency Telephone Number

Company Phone Number (901) 363-4340

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Flammable Aerosols	Category 1
Acute toxicity, inhalation	Category 4

Signal Word DANGER

Hazard Statements

Extremely flammable aerosol Harmful if inhaled.





Appearance Clear, colorless liquid

Physical State Liquid

Odor Pleasant

Precautionary Statements - Prevention

Use personal protective equipment as required

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Do not spray on an open flame or other ignition source

Pressurized container. Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 122°F.

Avoid breathing mist or vapor.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Get medical attention if irritation occurs

IF ON SKIN: Wash with plenty of soap and water

If skin irritation persists: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

Other Hazards

None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Aluminum Oxide	1344-28-1	Proprietary
Isobutane	75-28-5	Proprietary
Naptha (Petroleum), Hydrotreated Heavy	64742-58-9	Proprietary
Propane	74-98-6	Proprietary
Ammonium Hydroxide	1336-21-6	Proprietary

Product contains a proprietary mixture of ingredients.

4. FIRST AID MEASURES

First Aid Measures

General Advice If exposed or concerned: Get medical advice/attention. Provide this SDS to medical

personnel for treatment.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation occurs.

Skin Contact Flush with water while removing contaminated clothing and shoes before reuse. If irritation

persists, get medical attention.

Inhalation Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial

respiration if not breathing. If symptoms persist, call a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Do NOT induce vomiting. Seek medical attention immediately.

Most Important Symptoms and Effects, both Acute and Delayed

Symptoms Liquid in eyes can cause pain and irritation. Corneal injury likely. May cause skin and eye

irritation. Ingestion may result in irritation of mouth and gastrointestinal tract. Vomiting may cause chemical pneumonia. Overexposure by inhalation can cause irritation of the respiratory tract and adverse effects on the central nervous system. High concentrations or

prolonged exposure can cause unconsciousness and death.

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, or carbon dioxide.

Unsuitable Extinguishing Media Do not use water jet as an extinguisher, as this will spread fire.

Specific Hazards Arising from the Chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact

with skin and eyes and inhalation of vapors.

Methods and Material for Containment and Cleaning Up

Methods for Containment Prevent further leakage or spillage if safe to do so. Absorb liquid with sawdust, sand or

industrial absorbent.

Methods for Cleaning Up Sweep up absorbed material and shovel into suitable containers for disposal. Discard any

product, residue, disposable container or liner in full compliance with federal, state, and

local regulations. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling

Pressurized container. Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dray. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Ground and bond containers when transferring material. Do not re-use empty containers. Avoid contact with skin, eyes or clothing. Avoid breathing vapors. Avoid breathing mists. Use only in well-ventilated areas. Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Keep in

properly labeled containers. Store locked up.

Incompatible Materials Oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isobutane	STEL: 1000 ppm	-	TWA: 800 ppm
75-28-5			TWA: 1,900 mg/m ³
Aluminum Oxide	TWA: 1 mg/m ³	TWA: 15 mg/m ³	
1344-28-1		TWA: 5 mg/m ³	=
		PEL: 10 mg/m ³	
		PEL: 5 mg/m ³	
Propane	-	TWA: 1,000 ppm	TWA: 1,000 ppm
74-98-6		TWA: 1.800 mg/m ³	TWA: 1 800 mg/m ³

Appropriate Engineering Controls

Engineering ControlsVentilation must be adequate to maintain the ambient workplace atmosphere below the

exposure limit(s) outlined in the SDS.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection Goggles or face shield.

Skin and Body ProtectionWear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact. Wear protective Neoprene™ gloves, Rubber

gloves.

Respiratory ProtectionUse self-contained breathing apparatus if there is a heavy vapor about 300 ppm.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands after

use and wash contaminated clothes before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Estimated

Information on Basic Physical and Chemical Properties

Liquid / aerosol **Physical State Appearance** Clear liquid

Odor Not available Color Colorless Not determined **Odor Threshold**

Property Values Remarks • Method

рΗ Not determined

Melting Point/Freezing Point Not determined **Boiling Point/Boiling Range** 852.29°F (455.72°C)

Flash Point Propellant estimated -99.4°F (-73.0°C)

Evaporation Rate >1

Flammability (Solid, Gas) Not determined

Upper Flammability Limits 5% **Lower Flammability Limit** 0.7%

22.16 psig @70°F **Vapor Pressure** Estimated

Vapor Density Not determined

Specific Gravity 1.267 (1=Water)

Water Solubility Soluble in water **Solubility in Other Solvents** Not determined **Partition Coefficient** Not determined

Autoignition Temperature Estimated 440.02°F (226.68°C)

Decomposition Temperature Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Avoid heat, sparks, open flames and other ignition sources.

Incompatible Materials

Strong oxidizing agents, nitrates, fluorine, chlorine.

Hazardous Decomposition Products

No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

Eye Contact Direct contact with eyes may cause temporary irritation.

Skin Contact No irritation expected.

Inhalation Harmful if inhaled.

Ingestion Expected to be a low ingestion hazard.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isobutane 75-28-5	= 5,800 mg/kg (Rat)	-	= 1,237 mg/L (Mouse) 120 min = 1,355 mg/L (Rat) 4 h
Aluminum Oxide 1344-28-1	= > 2000 mg/kg (Rat)	-	= > 0.888 mg/L (Rat) 4 h
Propane 74-98-6	-	-	= 1,237 mg/L (Mouse) 120 min = 1,355 mg/L (Rat) 4 h
Naptha (Petroleum), Hydrotreated Heavy 64742-48-9	= 4,820 mg/kg(Rat)	= 1,900 mg/L (Rabbit) 24 hrs	= > 5,000 mg/L (Rat) 4 h

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Germ Cell Mutagenicity None.

Carcinogenicity None.

STOT - Single Exposure May cause drowsiness or dizziness.

Chronic Toxicity Prolonged inhalation may be harmful.

Aspiration Hazard Not likely.

Numerical Measures of Toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ammonium Hydroxide		15: 96 h Gambusia affinis		0.66: 48 h Daphnia magna
1336-21-6		mL/L LC50		mg/L EC50 Static

Persistence and Degradability

Not determined.

Bioaccumulation

Mobility

No data available.

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of WastesDisposal should be in accordance with applicable regional, national and local laws and

regulations. Do not puncture, incinerate, or crush.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations. Do not puncture, incinerate, or crush.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Packing Group N/A

<u>IATA</u>

UN/ID NoUN1950Proper Shipping NameAerosolsHazard Class2.1Packing GroupN/A

IMDG

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Packing Group N/A

15. REGULATORY INFORMATION

International Inventories

Not Determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

CERCLA

Not determined.

SARA 313

Not determined.

CAA (Clean Air Act)

Propane, CAS No. 74-98-6

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Isobutane 75-28-5	X	X	X
Aluminum Oxide 1344-28-1	Х	Х	X
Propane 74-98-6	Х	Х	X
Ammonium Hydroxide 1336-21-6	Х	Х	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	1	4	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	4	0	Not determined

Revision Date 5-March-2019 **Revision Note** New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet