



651B-ES XHD CONCENTRATE

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947



- Dynamic removal of grease bonded soils.
- Instantly soluble
- Unequaled in high speed cleaning power.

ELIMINATES CLOGGING

of coils and solution metering pumps caused by insoluble powder particles.

FAST - Balanced alkalinity, chelating and wetting power rapidly solubilizes tenacious, baked-on, grease-bonded soils. Cuts cleaning time by 25% or more.

ENDS CLOGGED COILS - caused by lime scale. Water-softening ingredients hold hard water minerals in harmless suspension prohibiting scale build-up.

NON-TOXIC - Non-flammable, no chromates or phenol. Requires only the same industrial care accorded any other highly alkaline product.

HEAVY DUTY - Fast removal of multiple coats of paint, if desired. Simply double or triple the recommended grease dissolving solutions.

ECONOMICAL - No inert fillers. Only 1 or 2 quarts required to charge a typical 10 gallon solution tank. Low material cost combined with labor and time savings.

DO NOT USE ON SOFT METALS SUCH AS ALUMINUM

NOTE

Foremost 651 B-ES is approved and recommended for all makes of steam cleaners and steam generating units.

Packed in 55 Gallon Drums

Rev. 5-2-14

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com





TECHNICAL DATA

FOREMOST 651B-ES XHD CONCENTRATE

Rev. 5-19-16

DESCRIPTION: A highly concentrated alkaline product designed for the fast and efficient removal of paint, heavy deposits of grease, oil and dirt from equipment and machinery. It is recommended exclusively for use on iron, steel, copper and ferrous alloyed surfaces; It will attack soft metals such as aluminum, zinc, tin, galvanized, babbitt or bearing metal. This compound cleans quickly and thoroughly by the combined chemical and physical action of penetration, saponification and detergency.

APPLICATION: Recommended for use in all types of pressure steam generating equipment. It is suggested for heavy duty cleaning of farm equipment, road machinery and other heavy mechanical units. This product is extensively used in renovating operations involving automatic and industrial equipment. It is also highly effective in removing asphaltic and petroleum residues from concrete floors as well as the compartments of tanks, barges and other marine vessels.

DIRECTIONS:

Heavy Duty Steam Cleaning: Normally 1 to 2 quarts per 10 gallons of solution is adequate.

Paint Stripping: Usually 2 to 5 gallons per 5 gallons of water is necessary, depending upon type and thickness of paint.

Cleaning Concrete Floors: For removal of soil, grease and motor oil from unpainted concrete floors use approximately 1 pint per 4 or 5 gallons of hot water, brush and rinse.

NOTE: Concentrations of Foremost 651B-ES XHD Concentrate may be lowered or increased to meet accepted individual requirements.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN. CONTAINS POTASSIUM HYDROXIDE AND SODIUM SILICATE.** Causes severe burns to eyes and skin. Do not get in eyes, on skin, or clothing. Do not take internally. Wash thoroughly after handling. When handling, always wear chemical splash goggles, face shield, rubber gloves and protective clothing.

FIRST AID: EYES AND SKIN: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. See physician immediately. Remove contaminated clothing and shoes. Wash clothing before reuse. Destroy contaminated shoes. **INGESTION:** If swallowed do not induce vomiting. If person is conscious, give large quantities of water or milk, if available. Get medical attention immediately.

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.

FACTS

1. Liquid
2. Highly caustic
3. Rapid penetration
4. Excellent soil suspension
5. Non-toxic
6. Non-flammable
7. Improved rinsability
8. Improved sequestration

BENEFITS

1. Economical and readily soluble
2. Very highly alkaline and contains enough caustic to perform light paint stripping
3. Very fast acting
4. Prevents redepositing of removed soils
5. Safe to use as directed
6. Safe around open fires
7. Leaves a film free surface
8. Water is softened and eliminates hard water build up in the steamer