



**693-ES**  
**ZING**  
CONCRETE REMOVER

**SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947**

**BEFORE**



**HARDENED CONCRETE**

**ZING**  
**AWAY**  
**CONCRETE**  
**and**  
**CEMENT**  
**FILMS**



**AFTER**



**LIKE-NEW TRUCK**

***KEEPS READY MIX TRUCKS LIKE NEW!***

**FAST-ACTING** — Works quickly to loosen stubborn deposits. Periodic use will eliminate destructive hammering and chiseling. Deposits over 1/16" should be removed mechanically, but use Foremost 693-ES to remove portion next to paint or metal to avoid denting surface.

**EFFECTIVE** — Strong solutions of Foremost 693-ES can be used on most paints and signs without harm. Should there be any evidence of unsound paint (dimming or bleeding), simply dilute with more water.

**PLEASANT ODOR** — The strong, penetrating acid odor of most concrete removers has been overcome with Foremost 693-ES. Its pleasing odor is more conducive to use by personnel.

**PACKAGED IN 55 GALLON DRUMS**

**ECONOMICAL** — Foremost 693-ES is furnished as a concentrate — low per gallon cost. Dilute with 2 to 4 parts tap water for economy. Stronger solutions are used on chutes and adjacent rear end areas. Foremost 693-ES saves time and labor in these critical areas.

**ENTHUSIASTICALLY RECOMMENDED FOR:**

Trucks	Mixers	Brick &	Forms
Pavers	Chutes	Masonry	Pallets
Spreaders	Conveyors	Clean-Up	

**CONTAINS NO CFC'S OR OTHER OZONE  
DEPLETING SUBSTANCES**

Authorized by USDA for use in federally  
inspected meat and poultry plants.

Rev. 12-09-13

Toll Free: 800-238-5150  
Local: 901-363-4340  
Fax: 901-375-3600

**Delta Foremost Chemical Corp.**  
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:  
[www.deltaforemost.com](http://www.deltaforemost.com)



# TECHNICAL DATA

## FOREMOST 693-ES ZING CONCRETE REMOVER

Rev. 3-7-17

- DESCRIPTION:** A highly acidic liquid concentrate especially designed for efficient and thorough removal of oxidation and concrete formations from iron, steel, copper and ferrous alloys.
- APPLICATION:** Recommended for use on exterior and interior surfaces of stationary concrete mixers, ready-mix trucks, paving machines, concrete pallets, and other equipment where accumulations of concrete and oxidation occur.
- DIRECTIONS:** Prepare a mixture of concentrate and water in suitable container. (See #3 Below) Usually 1 part to 3 or 4 parts water will be sufficient, but stronger or weaker solutions may be made to suit the severity of the encrustations.
- EXTERIOR SURFACES:** Apply only to oxidized areas or to concrete formations with a long-handled brush or mop. Allow to sit for a few minutes then flush with a water hose or steam gun. Follow with application of Foremost 528 Slix-Cote for inhibiting action, masking and prevention of further hardened concrete formations.
- INTERIOR SURFACES:** For removal of heavily encrusted concrete formations on the inside of drums on both stationary mixers and ready-mix trucks, charge with a solution of approximately 1 part concentrate to 1 to 4 parts water. Allow drum to revolve several minutes then inspect before draining. Increase time and/or repeat treatment as necessary. Drain and rinse thoroughly with water.
- SMALL PARTS, PALLETS, ETC.:** Immerse several minutes in vat of solution, remove and flush with water. Vat should be constructed of crockery, glass, wood, rubber, acid resistant brick or plastic. Neutralization is unnecessary if repainting or refinishing is desired.
- PRECAUTIONS:** **KEEP OUT OF REACH OF CHILDREN.** Contains hydrochloric acid. Causes severe eye and skin burns. Do not get in eyes, on skin, or clothing. Causes severe respiratory tract irritation. Do not breathe vapors. Vapor extremely irritating. Use with adequate ventilation. Do not take internally. When handling always wear chemical splash goggles, face shield, rubber gloves and protective clothing.
- FIRST AID: EYES AND SKIN:** In case of contact, immediately flush with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes under shower. Get medical attention immediately. **INGESTION:** If conscious, give large amounts of lime water or milk of magnesia or water. Get medical attention immediately. **INHALATION:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
- Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.

### FACTS

1. Economical concentrate
2. Minimized odor
3. Works quickly
4. Effective action

### BENEFITS

1. Cuts down or eliminates destructive hammering and chiseling.
2. Personnel are encouraged by the reduction in harshness and gagging acid odor.
3. May be diluted with water to suit the job to be done.
4. May be used full strength if needed with no harm done.