



# 695-ES SLEDGE HAMMER

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

## DESIGNED FOR EQUIPMENT RENTALS



Before Treatment



After . . . surfaces are free of concrete residue, in as little as 30 minutes.

### FOR THE REMOVAL OF HARDENED, CURED CONCRETE FROM RENTAL EQUIPMENT

**Foremost 695-ES Sledge Hammer** is formulated specifically for use by rental equipment companies for the removal of hardened cement residues from all types of rental equipment.

**SAVES LABOR**—Reduces man hours required for cleanup of equipment (Ex: 30 minutes to clean a buggy vs 3 hours if cleaning with conventional methods).

*Cleaning time is considerably shortened when temperature is above 70°F*

**VERSATILE**—Removes: concrete, dry wall, mortar, stucco, and grout.

#### SAFE FOR USE ON PAINTED SURFACES

- Plastic
- Rubber
- Aluminium
- Unpainted steel
- Fiberglass
- Glass
- Magnesium

**Packed in 55 Gallon Drums**

Rev. 1-20-14

Toll Free: 800-238-5150  
Local: 901-363-4340  
Fax: 901-375-3600

**Delta Foremost Chemical Corp.**  
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:  
[www.deltaforemost.com](http://www.deltaforemost.com)





# TECHNICAL DATA

## FOREMOST 695-ES SLEDGE HAMMER

Rev. 1-20-14

**DESCRIPTION:** A ready to use formula for REMOVING HARDENED OR CURED CONCRETE RESIDUES, MORTAR, CEMENT BASED STUCCO, AND SANDED GROUT. Safe for use on painted surfaces, aluminum, steel, brick, wood, plastic, fiberglass, and rubber.

**DIRECTIONS:** **Step 1:** Apply Sledge Hammer through any acid-safe spray equipment. May be used straight or cut 1 to 1 with water depending on surface to be cleaned.

**Step 2:** Depending on thickness of deposits, age and temperature, allow to stand for 15 minutes to two hours or longer.

**Step 3:** Pressure rinse or use hot water to remove.

If some material remains, repeat STEPS 1 through 3.

**NOTE: Cleaning time is considerably shortened when temperature is above 70°F.**

**PRECAUTIONS:** **KEEP OUT OF REACH OF CHILDREN.** Contains organic acid. Causes severe eye and skin burns. Do not get in eyes, on skin, or on clothing. Causes severe respiratory tract irritation. Do not breathe vapors. Vapor extremely irritating. Use with adequate ventilation. Do not take internally. When handling, always wear chemical splash goggles, face shield, rubber gloves and protective clothing.

**FIRST AID: EYES AND SKIN:** In case of contact, immediately flush with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes under shower. Get medical attention immediately. **INHALATION:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. **INGESTION:** If conscious, give large amounts of lime water or milk of magnesia or water. Get medical attention immediately.

Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.

### FACTS

1. Fast.
2. Ready to use.
3. Inhibited.
4. Economical.

### BENEFITS

1. Reduces clean-up time by as much as 75%.
2. May be used successfully by unskilled labor.
3. Does not harm painted surfaces, aluminum or steel.
4. Helps gets equipment back into the field faster.